

HADALAN® DQ0712 89M



**Decorative quartz for decorative surface designing, 0,7
- 1,2 mm**

Characteristics

HADALAN® DQ0712 89M is a light-fast, abrasion-resistant decorative quartz for the production of hard-wearing surfaces.

- light-fast
- colour-stable
- abrasion-resistant
- weatherproof

Use

HADALAN® DQ0712 89M is used together with the relevant HADALAN® binder to produce decorative coatings applied with a trowel or for scatter coverings, both indoors and outdoors.

Applications

- balcony and terraces
- indoor floors
- exterior stairs and staircases
- mineral substrates

Specifications

| | |
|------------------------|----------------|
| Packaging | paper bag |
| Bag size | 25 kg |
| No. of bags per pallet | 40 packs/pal. |
| Colour | grey |
| Grain size | 0.7 – 1.2 mm |
| Storage | dry, 24 months |

Quantity required

| | |
|----------------|-------------------------|
| Scatter-finish | 3 - 4 kg/m ² |
| Trowel-finish | ca. 7 kg/m ² |

HADALAN® DQ0712 89M

Preparation of the surface

The substrate must be capable of bearing a load, surface-dry and free of dirt, dust, residues of detergents or other substances which limit adhesion.

In the case of severe changes in temperature together with increased levels of humidity there is a danger that condensation could form on the substrate.

Before starting to apply the coating therefore, any film of water must have completely dried out.

Application

1. Scatter surfaces

Apply **HADALAN® PUR Top 32P transparent** as an adhesive layer.

2. Sprinkle (scatter) **HADALAN® DQ0712 89M** section by section, using more than you actually need (in other words, using a surplus amount of material), directly on to the fresh adhesive layer which you have just applied. Make sure that you cover the complete area.

3. On the next day brush off or suck off any surplus quartz which has not bonded. Then apply **HADALAN® Pur Top 32P** with a mohair roller.

1. Trowel surfaces:

Pre-coat the surface with **HADALAN® PUR Top 32P transparent**. Lightly scatter (sprinkle) oven-dried **Quartz051 57M** into the still-fresh coating. This coating must dry because it ensures that the following trowelling working will have sufficient grip.

2. Add 6% of **HADALAN® LF68 12P** to the **HADALAN® DQ0712 89M** and mix thoroughly using a slow-running drilling machine. Then transfer to a clean container and briefly stir through again.

3. With a trowel, spread the mixture, section by section, and then compact it with a smoothing trowel.

4. For more detailed information please refer to the relevant technical data sheets or the application instructions for repairing, coating and applying decorative surfaces contained in the leaflet "Sanierung, Beschichtung" und dekorative Gestaltung mit HADALAN® PUR-Flüssigkunststoffen.

hahne system products

HADALAN® LF68 12P

HADALAN® EPV 38L

HADALAN® PUR Top 32P transparent

Quartz051 57M

Important notes

- Make sure you follow our application instructions or the relevant technical data sheets.
- If you are treating an area which needs to look identical from an optical point of view, then make sure you use decorative quartz from the same batch. If you use different batches there could be some differences in the shade.

Ingredients

Decorative quartzes

Safety provisions/recommendations

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG

Mühlenschweg 6, 49090 Osnabrück

Tel +49 2363 5663-0, Fax +49 2363 5663-90

hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 12.2020