

Marble stones for decorative surface designing, 2 - 4 mm

Characteristics

HADALAN® MST 89M are lightfast, abrasion-resistant stone fractions for making high-quality floorings. A special surface treatment is used to break the edges and corners of the stones to make them very easy to use.

- Light fast
- Colourfast
- Abrasion resistant
- Weatherproof
- Natural colours

Use

Mixed with the appropriate HADALAN® Binder, **HADALAN® MST 89M** are used for producing decorative non-slip scratch coatings for indoors and outdoors.

Applications:

- Balconies, patios and terraces
- Interior floors
- Exterior steps and stairs
- Mineral substrates

Specifications

Packaging	PE sack
Pack	25 kg
Supplied	42 packs/pal.
Particle size	2-4 mm
Colours	grey, green, rosé, white, black, brown-grey, bordeaux, terracotta, light beige, maroon, light grey, brown-cream, anthracite, grey-beige, brown-mixed, gray-cream
Storage	dry, 24 months
Quantity required	
Grain size 2 – 4 mm for 8 mm layer thickness	approx. 12 kg/m ²

Preparation of the surface

The substrate must be sound, with a dry surface and free from dirt, dust, cleaner residues or other adhesion reducing substances.

Where there are marked temperature changes in connection with increased relative humidity, there is a risk of condensation collecting on the substrate surface. Before starting work on coating, this water film must be completely dried off.

Application

1. Depending on the application, **HADALAN® MST 89M** are mixed with 3.5 - 7 % binder. Pre-tests should be carried out as required.
2. The stirred trowel mix is spread evenly on the prepared surface and smoothed down and compacted in a homogeneous manner with a smoothing trowel.
3. Clean tools with **HADALAN® EPV 38L** immediately after use.
4. Please find details in the appropriate technical data sheets and the application instructions "Renovation, coating and decorative design with HADALAN® PUR liquid plastics."

hahne system products

HADALAN® BM1K 32P
HADALAN® LF68 12P
HADALAN® EPV 38L

Important notes

- Follow the notes in our application instructions and appropriate technical data sheets.
- Use **HADALAN® EPV 38L** from a single batch to obtain visually similar surfaces. Using different batches can lead to colour variations.
- When laying ensure that the drainage level has a sufficient slope, so that the natural stone covering can drain properly and no puddles can form.

Ingredients

Natural stone

Safety provisions/recommendations

No special measures necessary.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 12.2020