

## Decorative quartz for decorative surface designing, 0.3 - 0.8 mm

### Characteristics

**HADALAN® DQ0308 89M** is light-resistant, abrasion-resistant decorative quartz for making appealing ground linings.

- Light-resistant
- Colour-fast
- Abrasion resistant
- Weathering-resistant

### Use

**HADALAN® DQ0308 89M** is used in conjunction with the respective HADALAN® bonding agent for creating decorative, scatter coverings indoors and outdoors.

### Application areas:

- Balcony and terrace surfaces
- Floor surfaces, indoors
- Outside staircases
- Mineral substrates

### Specifications

Packaging	Paper bag
Container	25 kg
Delivery form	40 sacks/pallet
Colour shade	Grey, blue/grey
Grain size	0.3 – 0.8 mm
Storage	dry, 12 months

### Quantity required

Scattered covering	3 - 4 kg/m <sup>2</sup>
--------------------	-------------------------

## Preparation of the surface

The substrate must be load-bearing, surface dry and free of dirt, dust, cleaning agent residues or other separating substances.

During periods of strong temperature fluctuations related to higher humidity, there is a danger of condensation water build up on the substrate surface. Before beginning with the coating work, this water film must be completely dried off.

## Application

Scattered covering with **HADALAN® MBH 12E**:

1. Apply **HADALAN® MBH 12E** as an adhesive layer with approx. 0.3 kg/m<sup>2</sup>.
2. **HADALAN® DQ0308 89M** to be scattered in generous quantities directly in the fresh adhesive layer.
3. After drying, sweep away or vacuum off quartz that has not been integrated.

Subsequently seal with **HADALAN® MBH 12E** using a mohair roller with approx. 0.5 kg/m<sup>2</sup>.

Scattered covering with **HADALAN® PUR Top 32P transparent**:

1. Apply **HADALAN® PUR Top 32P transparent** as an adhesive layer with approx. 0.3 kg/m<sup>2</sup>.
2. **HADALAN® DQ0308 89M** to be scattered in generous quantities directly in the fresh adhesive layer, approx. 3 kg.
3. After drying, sweep away or vacuum off quartz that has not been integrated.

Subsequently seal with **HADALAN® PUR Top 32P transparent** using a mohair roller with approx. 0.5 kg/m<sup>2</sup>.

## hahne system products

HADALAN® MBH 12E

HADALAN® EPV 38L

HADALAN® PUR Top 32P transparent

Quartz051 57M

## Important notes

- Note the instructions in our processing instructions or the respective technical codes of practice.
- For a surface that visually belongs together, use decorative quartz from one batch. Colour variance is possible if different batches are used.

## Ingredients

Decorative quartz

## Safety provisions/recommendations

No special steps required.

## Disposal

The local waste removal regulations must be observed.

## Manufacturer

**Sievert Baustoffe GmbH & Co. KG**

Mühlenschweg 6, 49090 Osnabrück

Tel +49 2363 5663-0, Fax +49 2363 5663-90

hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 12.2020