

Post-treatment agent for fresh concrete

Characteristics

HADALAN® C 10D is a transparently drying fresh concrete protective agent with a plastic dispersion base. It prevents the premature evaporation of the mixing water, reduces the shrinkage cracking tendency and increases the compression strength and the bending tensile strength of the cement, thanks to the sufficiently longer hydration.

It does not hamper the adhesion of the following coats and does not have an unpleasant odour.

- Solvent-free
- Prevents drying out
- Transparent
- Improves the hydration progression
- Reduces tendency to shrinkage cracks

Use

HADALAN® C 10D for post-treatment and improving the hydration progression of the fresh concrete.

As protection against an air draft, strong sunlight and low atmospheric humidity.

Area of application:

- New concrete

Specifications

Packaging	PE canister
Barrel	20 kg
Delivery form	24 canisters/pallet
Processing temperature	+5 °C to +35 °C
Density	1.92 kg/l
Storage	frost-free, minimum 12 month

Quantity required

Per application quantity	0.15 - 0.2 kg/m ²
--------------------------	------------------------------

Application

1. **HADALAN® C 10D** should be stirred well before use.
2. Brush on or spray on the material undiluted immediately after the concreting, on the fresh concrete.
3. Clean all processing equipment with water immediately after use.

At very high ambient temperatures, the given application quantities should be increased.

Important notes

- Maintain the processing temperature of +5 °C to +35 °C.
- Before application, the concrete or screed should not have been bonded.
- With surfaces subjected to free weathering, some slight yellowing should be expected.

Ingredients

Plastic dispersion

Safety provisions/recommendations

For detailed information regarding safety during transport, storage and handling, refer to the updated safety data sheet.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply.
Version as of 12.2020