

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** DAKORIT BK-Flex
- **Article number:** 50183 B
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation**
Solvent-based, elastoplastic sealant to the roof and joint sealing
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Heinrich Hahne GmbH & Co. KG
Heinrich-Hahne-Weg 11
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**
Abteilung: Produktsicherheit
Tel.: 02363 5663-0
EMail: info@hahne-bautenschutz.de
- **Emergency telephone number:**
Gif tinformationszentrum Nord (GIZ Nord) Universität Göttingen,
Tel.: 0551-19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified according to the CLP regulation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
- **Information concerning particular hazards for human and environment:**
R 10 Flammable.
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Hazard-determining components of labelling:** Naphtha (Erdöl), hydrodesulfuriert, schwer, <0,1% Benzol)
- **Risk phrases:**
10 Flammable.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Safety phrases:**
7 Keep container tightly closed.
24/25 Avoid contact with skin and eyes.
37 Wear suitable gloves.
51 Use only in well-ventilated areas.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

Trade name: DAKORIT BK-Flex

(Contd. of page 1)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Solvent-containing preparation based on bitumen.

- **Dangerous components:**

CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	< 25%
EINECS: 265-149-8	Xn R65; N R51/53 R10-66-67	
	Flam. Liq. 3, H226; Aquatic Chronic 2, H411	

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Get when symptoms or doubts, seek medical advice.
- **After inhalation:**
Fresh air, keep patient at rest. If breathing is irregular or stopped, give artificial respiration Consult a physician.
- **After skin contact:**
Remove contaminated clothing. Wash with soap and water or medical paraffin. Skin on brief.
- **After eye contact:** Immediately with plenty of water, paraffin oil DAB 8 instill, consult an ophthalmologist.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Due to the content of organic components (bitumen) from the burning dense black smoke. Inhaling the fumes can lead to serious health problems.
- **Advice for firefighters**
- **Protective equipment:** If necessary respiratory protection is required.
- **Additional information** Cool closed containers exposed to fire with water.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
The usual precautionary measures for handling chemicals should be observed.
Due to the organic solvents from sources of ignition and ventilate the room well. Do not inhale fumes.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Cover with absorbent material, and, after curing, scrape and sweep up.

(Contd. on page 3)

Trade name: DAKORIT BK-Flex

(Contd. of page 2)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
The usual precautionary measures for handling chemicals should be observed. Contact with eyes and skin. When using do not eat, drink or smoke. Container during breaks close. Personal protective orientation refer to point 8 Comply with the health and safety precautions should be observed.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Solvent vapors are heavier than air and may spread along floors.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Keep container tightly closed in a cool, well-ventilated place.
- **Information about storage in one common storage facility:**
Do not store near combustible materials. Keep away from highly acidic or alkaline materials as well as oxidizers.
- **Further information about storage conditions:** In the original container.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

8052-42-4 Asphalt (25-50%)

WEL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³
-----	--

64742-47-8 Distillates (petroleum), hydrotreated light (10-25%)

TRGS 900 Kurzzeitwert	500 mg/m ³ , 100 ppm
-----------------------	---------------------------------

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

- **Respiratory protection:**

Not required, if ventilation is sufficient. In poorly ventilated workplaces should respirator should be worn. Filter mask combination filter A-P2.

- **Protection of hands:** Solvent resistant gloves only.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Solvent-resistant gloves made of neoprene rubber, nitrile rubber, Viton, PVA, butyl rubber, or equivalent.

(Contd. on page 4)

Printing date 14.05.2013

Revision: 12.04.2013

Trade name: DAKORIT BK-Flex

(Contd. of page 3)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Wear safety goggles when transferring and splashing hazard.
- **Body protection:**
Wear clothing made of natural fibers, otherwise there is the possibility of the electrostatic charge.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	pasty
Colour:	Black
Odour:	Solvent-like
- **pH-value:** n.a.
- **Change in condition**

Melting point/Melting range:	-15°C
Boiling point/Boiling range:	Undetermined.
- **Flash point:** 41°C
- **Ignition temperature:** 210°C
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** The product is not explosive, but the formation of explosive air / vapor mixtures are possible.
- **Explosion limits:**

Lower:	0.3 Vol %
Upper:	6.5 Vol %
- **Vapour pressure at 20°C:** 2 hPa (ASTM 323)
- **Density at 20°C:** 1.1 g/cm³
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Viscosity:**

Dynamic at 20°C:	360000 mPas
------------------	-------------
- **Solvent content:**

Organic solvents:	<25 %
-------------------	-------
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Keep away from strong acids and alkalics, halogens and strong oxidants.

GB

(Contd. on page 5)

Printing date 14.05.2013

Revision: 12.04.2013

Trade name: DAKORIT BK-Flex

(Contd. of page 4)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Dries skin.
- **on the eye:** can cause eye discomfort
- **Sensitization:** No sensitizing effects known.
- **Other information (about experimental toxicology):**
When handled and used properly, no adverse health effects are expected. Skin irritation with prolonged exposure possible. Prolonged inhalation may cause headache, dizziness and fatigue.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
17 03 02	bituminous mixtures other than those mentioned in 17 03 01

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---------------------------------------|-----------------|
| · UN-Number | - |
| · UN proper shipping name | - |
| · Transport hazard class(es) | - |
| · Packing group | - |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |

(Contd. on page 6)

Printing date 14.05.2013

Revision: 12.04.2013

Trade name: DAKORIT BK-Flex

(Contd. of page 5)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*

· **Transport/Additional information:**

· **ADR**

· **Remarks:** *Not hazardous according to the ADR*

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
III	23

· **Other regulations, limitations and prohibitive regulations TRGKS 404, Group 2**

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 *Flammable liquid and vapour.*

H411 *Toxic to aquatic life with long lasting effects.*

R10 *Flammable.*

R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

R65 *Harmful: may cause lung damage if swallowed.*

R66 *Repeated exposure may cause skin dryness or cracking.*

R67 *Vapours may cause drowsiness and dizziness.*

· **Abbreviations and acronyms:**

ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

GHS: *Globally Harmonized System of Classification and Labelling of Chemicals*

GB