

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** HADALAN EG145 13E, Komp. A
- **Article number:** 50258 B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Rapid-hardening, two-component epoxy resin for priming mineral substrates with risk of moisture penetration from the back surface.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Heinrich Hahne GmbH & Co. KG  
Heinrich-Hahne-Weg 11  
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**  
Abteilung: Produktsicherheit  
Tel.: 02363 5663-0  
Email: [info@hahne-bautenschutz.de](mailto:info@hahne-bautenschutz.de)
- **1.4 Emergency telephone number:**  
Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,  
Tel.: 0551-19240

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.  
Eye Irrit. 2      H319 Causes serious eye irritation.  
Skin Sens. 1      H317 May cause an allergic skin reaction.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

- **Hazard description:**

Xi Irritant

N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. May produce an allergic reaction.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Trade name: HADALAN EGI45 13E, Komp. A**

(Contd. of page 1)

· **Hazard pictograms**



GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  
Bisphenol-F Epichlorhydrinharz Reaktionspr. Phenol-Formaldehyd Novolak mit Epichlorhydrin  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· **Hazard statements**

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P262 Do not get in eyes, on skin, or on clothing.  
P273 Avoid release to the environment.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P360 Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· **Additional information:**

Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Epoxy resin.

· **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) ☒ Xi R36/38; ☒ Xi R43; ☒ N R51/53 ☒ Aquatic Chronic 2, H411; ☒ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	>50- <75%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ☒ Xi R38; ☒ Xi R43 ☒ Skin Irrit. 2, H315; Skin Sens. 1, H317	>10- <20%
CAS: 28064-14-4	Bisphenol-F Epichlorhydrinharz Reaktionspr. Phenol-Formaldehyd Novolak mit Epichlorhydrin ☒ Xi R36/38; ☒ Xi R43; ☒ N R51/53 ☒ Aquatic Chronic 2, H411; ☒ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	>10- <20%

· **Additional information:**

For the wording of the listed risk phrases refer to section 16.  
GISCODE: RE 1 (resin + hardener)

GB

(Contd. on page 3)

Trade name: **HADALAN EGI45 13E, Komp. A**

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Use fire extinguishing methods suitable to surrounding conditions.  
Foam ( alcohol resistant), carbon dioxide, dry powder, water spray.
- **For safety reasons unsuitable extinguishing agents:** Water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** In case of fire: breathing protection with independent air supply.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away non-protected persons. Ensure adequate ventilation.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Only store in original containers.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Protect from frost.
- **Information about storage in one common storage facility:** Store separate from eatables.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** VCI: 10
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Trade name: **HADALAN EGI45 13E, Komp. A**

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required if good ventilation.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
Use protective gloves. Nitrile gloves wear with a layer thickness of at least 0.4 mm.  
(Breakthrough time > 480 min -. Gisbau.de see also www)
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  
Wear safety gloves made of nitrile rubber with a thickness < 0.4 mm (penetration time > 480 min - see also www.gisbau.de
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed goggles
- **Body protection:** Protective clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	yellowish
<b>Odour:</b>	weak, characteristic
- **pH-value:** n.a.
- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	> 200 °C
- **Flash point:** ca. 140 °C
- **Ignition temperature:** 450 °C
- **Self-igniting:** Product is not selfigniting.

(Contd. on page 5)

**Trade name: HADALAN EGI45 13E, Komp. A**

(Contd. of page 4)

· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Vapour pressure at 50 °C:</b>	5 hPa
· <b>Density at 20 °C:</b>	1.12 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Viscosity:</b>	
· <b>Dynamic at 20 °C:</b>	600 mPas
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

· **10.3 Possibility of hazardous reactions**

Exothermic reactions with amines. Rapidly process after adding the hardener, as in the curing high temperatures can be reached.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:**

Before strongly acidic and alkaline materials as well as oxidizers away in order to avoid exothermic reactions.

· **10.6 Hazardous decomposition products:**

At higher temperatures may produce carbon dioxide, carbon monoxide and nitrogen oxides.

### SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitisation:** Sensitisation possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 6)

Printing date 27.05.2015

Revision: 27.05.2015

Trade name: **HADALAN EGI45 13E, Komp. A**




(Contd. of page 5)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
  - **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
  - **European waste catalogue**
- |           |   |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|-----------|---|
- **Uncleaned packaging:**
  - **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | UN3082   |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>         | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)), MARINE POLLUTANT<br>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))   |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG</b></li> </ul>  | <div style="display: flex; align-items: center; gap: 10px;">   </div> <p>· <b>Class</b> 9 Miscellaneous dangerous substances and articles.<br/>           · <b>Label</b> 9</p> <hr style="border-top: 1px dashed black;"/> <p>· <b>IATA</b></p> <div style="display: flex; align-items: center; gap: 10px;">  </div> <p>· <b>Class</b> 9 Miscellaneous dangerous substances and articles.</p> |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR</b></li> </ul>   | III  |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> <li>· <b>Special marking (ADR):</b></li> </ul> | Symbol (fish and tree)<br>Symbol (fish and tree)   |

(Contd. on page 7)

**Trade name: HADALAN EGI45 13E, Komp. A**

(Contd. of page 6)

· <b>Special marking (IATA):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles.
· <b>Danger code (Kemler):</b>	90
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
· <b>UN "Model Regulation":</b>	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Other regulations, limitations and prohibitive regulations**  
For activities involving exposure to uncured epoxy resins and contact on the skin or respiratory are causing regular preventive medical examinations.  
This product is subject to the Directive 2004/42/EC.  
EU limit value of this product is in ready to use condition: 500 g / l (2010). The product contains: 0 g / l VOC.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.  
-----  
R36/38 Irritating to eyes and skin.  
R38 Irritating to skin.  
R43 May cause sensitisation by skin contact.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 27.05.2015

Revision: 27.05.2015

**Trade name: HADALAN EGI45 13E, Komp. A**

*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*  
*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*  
*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*

(Contd. of page 7)

GB