

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** HADALAN FBA 32P
- **Article number:** 50343 A
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the preparation** Flexible balcony sealant, 1-component
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Heinrich Hahne GmbH & Co. KG  
Heinrich-Hahne-Weg 11  
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**  
Abteilung: Produktsicherheit  
Tel.: 02363 5663-0  
EMail: info@hahne-bautenschutz.de
- **Emergency telephone number:**  
Gif tinformationszentrum Nord (GIZ Nord) Universität Göttingen,  
Tel.: 0551-19240

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

- 
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
  - **Hazard description:** Xn Harmful
  - **Information concerning particular hazards for human and environment:**  
R 10 Flammable.  
R 20 Harmful by inhalation.  
R 42/43 May cause sensitisation by inhalation and skin contact.  
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Contains isocyanates. May produce an allergic reaction.  
Contains 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate. May produce an allergic reaction.
  - **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- 
- **Label elements**
  - **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.  
Flammable.
  - **Code letter and hazard designation of product:**



Xn Harmful

**Trade name: HADALAN FBA 32P**

(Contd. of page 1)

· **Risk phrases:**

- 10 Flammable.
- 20 Harmful by inhalation.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

- 23 Do not breathe vapour.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 37/39 Wear suitable gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Special labelling of certain preparations:**

- Contains isocyanates. May produce an allergic reaction.
- Contains 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate. May produce an allergic reaction.

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Preparation based on polyurethane prepolymer, containing solvents

· **Dangerous components:**

CAS: 93763-35-0 EINECS: 297-854-1	Hydrocarbons, C9-16, hydrotreated, dearomatized ☒ Xn R65 ☠ Asp. Tox. 1, H304	2.5-10%
CAS: 4098-71-9 EINECS: 223-861-6	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate ☠ T R23; ☒ Xn R42/43; ☒ Xi R36/37/38; ☠ N R51/53 ☠ Acute Tox. 3, H331; ☠ Resp. Sens. 1, H334; ☠ Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 0.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ☒ Xn R65; ☒ Xi R37; ☠ N R51/53 R10-66-67 Carc. Cat. 2, Muta. Cat. 2 ☠ Flam. Liq. 3, H226; ☠ Carc. 1B, H350; ☠ Asp. Tox. 1, H304	1.0-2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

(Contd. on page 3)

**Trade name: HADALAN FBA 32P**

(Contd. of page 2)

*Abundant Supply fresh air and call for doctor.*

*If unconscious, place and transport in stable lateral position.*

*Immediately dexamethasone spray (Auxilason, Pumocrt) inhale. Patient to fresh air, seek medical attention Inhalation.*

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

· **After eye contact:**

*Rinse opened eye for several minutes under running water and seek medical advice.*

*Eye for several minutes under running water with eyelids open. If symptoms persist, consult a doctor.*

*Unaffected eye protect, remove contact lenses.*

· **After swallowing:** *Drink plenty of water and provide fresh air. Call for a doctor immediately.*

· **Information for doctor:**

*Symptoms: After prolonged exposure to mild skin irritation possible. With aspiration can occur edema and pneumonia.*

*Irritating: on the skin and mucous membranes, has a narcotic effect. Decontamination, symptomatic treatment. After swallowing Induce vomiting or gastric lavage with enclosing administration of activated charcoal and sodium sulfate (each 1 tablespoon to 1/4 liter of water). Do not give adrenaline or its derivatives. A toxic pulmonary edema can be detected radiographically at an early stage in a chest x-ray about 8 hours after inhalation (perihilar opacities). For comparison, therefore, a chest radiograph is recommended as soon as possible after inhalation, if the risk of pulmonary edema is suspected.*

· **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*

· **Indication of any immediate medical attention and special treatment needed**

*No further relevant information available.*

## 5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** *Water spray, foam, powder, CO2*

· **For safety reasons unsuitable extinguishing agents:** *Water with full jet*

· **Special hazards arising from the substance or mixture**

*Case of fire, CO2, CO and nitrous gases possible.*

*Product reacts with water. Prevent ingress of water into the product and product containers - bursting through decomposition. Prevent spreading of vapors or product from reaching sewage system - risk of explosion. Spilled not burning product cover with foam. Affected by the fire cool, undamaged containers with water spray.*

· **Advice for firefighters**

· **Protective equipment:** *Mount respiratory protective device.*

· **Additional information** *Contaminated extinguishing water separately.*

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

*Wear protective equipment. Keep unprotected persons away.*

· **Environmental precautions:**

*Do not allow product to reach sewage system or any water course.*

*Inform respective authorities in case of seepage into water course or sewage system.*

*Do not allow to enter sewers/ surface or ground water.*

· **Methods and material for containment and cleaning up:**

*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*

*Dispose contaminated material as waste according to item 13.*

*Ensure adequate ventilation.*

*Clean on exit / discharge larger amounts of soil surface and discard.*

· **Reference to other sections**

*See Section 7 for information on safe handling.*

*See Section 8 for information on personal protection equipment.*

(Contd. on page 4)

**Trade name: HADALAN FBA 32P**

See Section 13 for disposal information.

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool, dry place.  
Keep ignition sources away.
- **Information about storage in one common storage facility:** Do not store with food, beverages and tobacco.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate (< 2.5%)**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**  
In inadequately ventilated places require respiratory protection. Recommendation: filter type A (B), possibly with P3.
- **Protection of hands:**  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  
Recommended: nitrile gloves or butyl rubber.

(Contd. on page 5)

**Trade name: HADALAN FBA 32P**

(Contd. of page 4)

- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

<b>Form:</b>	liquid
<b>Colour:</b>	according to product specification
<b>Odour:</b>	Type specific, according solvents

· **pH-value:** Not determined.

#### · Change in condition

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	162 °C

· **Flash point:** 24 °C

· **Flammability (solid, gaseous):** Not applicable.

#### · Ignition temperature:

**Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### · Explosion limits:

<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	7.5 Vol %

· **Vapour pressure at 20 °C:** 5 hPa

<b>Density at 20 °C:</b>	1.5 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.

· **Solubility in / Miscibility with water:** reacts with water

· **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity:

<b>Dynamic at 20 °C:</b>	4000 mPas
<b>Kinematic:</b>	Not determined.

· **Other information** No further relevant information available.

## 10 Stability and reactivity

### · Reactivity

#### · Chemical stability

#### · Thermal decomposition / conditions to be avoided:

Incomplete combustion of carbon monoxide, oxides of nitrogen. Violent reaction with strong oxidizing agents. Reacts with: amines, strong bases, alcohols, as well as elimination of CO<sub>2</sub> with water and carboxylic acids.

(Contd. on page 6)

**Trade name: HADALAN FBA 32P**

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Water, strong oxidizing agents, amines, alcohols, strong bases.
- **Hazardous decomposition products:**  
No decomposition if used according to specifications.  
In combustion emits toxic fumes of carbon monoxide, carbon dioxide.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**  
has a degreasing effect on the skin.  
Irritant
- **on the eye:** Irritant
- **Sensitization:**  
Sensitization possible through inhalation.  
Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Irritant

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Other information:** Forms solid reaction product with water.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**

(Contd. on page 7)



Printing date 02.07.2013

Revision: 02.07.2013

**Trade name: HADALAN FBA 32P**

(Contd. of page 6)

Must not be disposed together with household garbage. Do not empty into drains.  
Cover spillage with moist absorbent material (sand, sawdust, general-purpose binder). Record after about 1 hour transfer to waste container and do not seal (evolution of CO<sub>2</sub>). Keep moist and let stand in a safe place outdoors 7-14 days and then dispose of regulated waste.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number	-
· UN proper shipping name	-
· Transport hazard class(es)	-
· Packing group	-
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not hazardous according to ADR.

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Technical instructions (air):

Class	Share in %
I	0.2
NK	3.0

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Other regulations, limitations and prohibitive regulations**  
This product is subject to Directive 2004/42/EC.  
EU limit value for the VOC content of this product is ready for use: cat A / i 500 g / l (2010).  
The product contains a ready to use product: <190 g / l VOC.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.07.2013

Revision: 02.07.2013

**Trade name: HADALAN FBA 32P**

(Contd. of page 7)

- H334* May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
*H335* May cause respiratory irritation.  
*H350* May cause cancer.  
*H411* Toxic to aquatic life with long lasting effects.
- R10* Flammable.  
*R23* Toxic by inhalation.  
*R36/37/38* Irritating to eyes, respiratory system and skin.  
*R37* Irritating to respiratory system.  
*R42/43* May cause sensitisation by inhalation and skin contact.  
*R51/53* Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
*R65* Harmful: may cause lung damage if swallowed.  
*R66* Repeated exposure may cause skin dryness or cracking.  
*R67* Vapours may cause drowsiness and dizziness.

**Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GB