

Printing date 27.05.2015 Revision: 27.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: HADALAN FKFlex w 54Z

· Article number: 51006 B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Watertight, frost-resistant thin bed mortar for marble, stone-ware tiles and natural stone slabs

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Heinrich Hahne GmbH & Co. KG

Heinrich-Hahne-Weg 11

45711 Datteln

Tel.:02363/5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit

Tel.: 02363 5663-0

EMail: info@hahne-bautenschutz.de
• 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC
- · Hazard description: Xi Irritant
- · Information concerning particular hazards for human and environment:

R 37/38 Irritating to respiratory system and skin.

R 41 Risk of serious damage to eyes.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05

GHS07



Printing date 27.05.2015 Revision: 27.05.2015

Trade name: HADALAN FKFlex w 54Z

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

Cement, portland, chemicals

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention. P302+P352 *IF ON SKIN: Wash with plenty of soap and water.*

- · 2.3 Other hazards Labeled 'Irritant' occurs only in contact with water (alkaline reaction)
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: cementitious powder reaction

.]	Dangerous	components	•
-----	-----------	------------	---

CAS: 65997-15-1 Cement, portland, chemicals

Xi R37/38-41 EINECS: 266-043-4 📀 Eye Dam. 1, H318; 🕦 Skin Irrit. 2, H315; STOT SE 3, H335

· Additional information: Solvent: ZP1

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

not applicable, product is not flammable

Fire-fighting measures must be adapted to fire.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

25-50%



Printing date 27.05.2015 Revision: 27.05.2015

Trade name: HADALAN FKFlex w 54Z

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: Use self-contained breathing apparatus

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Prevent formation of dust.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions: Store in a cool, dry place.
- · Storage class: VCI storage class: 13 Non-hazardous solid brand.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with	limit values th	at require mo	nitoring at the	e workplace:
--------------------	-----------------	---------------	-----------------	--------------

65997-15-1 Cement, portland, chemicals (10-25%)

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

14808-60-7 Quartz (SiO2) (50-100%)

WEL 0.15 A mg/m³ 24; (DFG)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use dust mask if dust is produced.

Leaflet ZH1/134 professional association

(Contd. on page 4)



Printing date 27.05.2015 Revision: 27.05.2015

Trade name: HADALAN FKFlex w 54Z

(Contd. of page 3)

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Leaflet ZH 1/134 main dealer association d. BG

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves made of PVC, rubber, nitrile rubber.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Wear protective goggles when dust and splashes.
- · **Body protection:** Suitable protective clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid
Colour: white
• Odour: Odourless

• pH-value (100 g/l) at 20 °C: 11-13

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

• Flash point: Not applicable.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Density: Not determined.

· Solubility in / Miscibility with

water: Dispersible.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)



Printing date 27.05.2015 Revision: 27.05.2015

Trade name: HADALAN FKFlex w 54Z

(Contd. of page 4)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitisation: As long as the expiration date is exceeded, is not expected to have a sensitizing effect.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

17 01 01 | concrete

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	-	
· 14.2 UN proper shipping name	-	
· 14.3 Transport hazard class(es)	-	
· 14.4 Packing group	-	

-GB



Printing date 27.05.2015 Revision: 27.05.2015

Trade name: HADALAN FKFlex w 54Z

	(Contd. of page 5)
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	No dangerous good under transport regulations

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- GB