

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** HADALAN FV 12P
- **Article number:** 50315 B
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the preparation**  
Colour deepener for colour intensification of HADALAN® natural stone putty mixtures with HADALAN® NSK 20D
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Heinrich Hahne GmbH & Co. KG  
Heinrich-Hahne-Weg 11  
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**  
Abteilung: Produktsicherheit  
Tel.: 02363 5663-0  
Email: info@hahne-bautenschutz.de
- **Emergency telephone number:**  
Gif tinformati onszentrum Nord (GIZ Nord) Universität Göttingen,  
Tel.: 0551-19240

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Sens. 1      H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
- **Hazard description:** Xi Irritant
- **Information concerning particular hazards for human and environment:**  
R 43 May cause sensitisation by skin contact.  
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Contains isocyanates. May produce an allergic reaction.

- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### · Label elements

- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**



Xi Irritant

- **Hazard-determining components of labelling:** Aliphatisches Polyisocyanat

**Trade name: HADALAN FV 12P**

(Contd. of page 1)

· **Risk phrases:**

- 43 May cause sensitisation by skin contact.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

- 24/25 Avoid contact with skin and eyes.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
36/37 Wear suitable protective clothing and gloves.  
46 If swallowed, seek medical advice immediately and show this container or label.

· **Special labelling of certain preparations:** Contains isocyanates. May produce an allergic reaction.

· **Other hazards**

· **Results of PBT and vPvB assessment**









- **PBT:** Not applicable.  
· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Preparation based on aliphatic polyisocyanates.

· **Dangerous components:**

CAS: 28182-81-2	Aliphatisches Polyisocyanat  Xi R43 R52/53 -----  Skin Sens. 1, H317; Aquatic Chronic 3, H412	50-100%
CAS: 822-06-0 EINECS: 212-485-8	hexamethylene diisocyanate  T R23;  Xn R42/43;  Xi R36/37/38 -----  Acute Tox. 3, H331;  Resp. Sens. 1, H334;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 0.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 3)

**Trade name: HADALAN FV 12P**

(Contd. of page 2)

### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
Use fire fighting measures that suit the environment.  
Foam, carbon dioxide, dry chemical, water fog, water spray jet.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet.
- **Special hazards arising from the substance or mixture**  
Possible formation of carbon monoxide, nitrogen oxide, isocyanate vapors and traces of hydrogen cyanide in fires.
- **Advice for firefighters**
- **Protective equipment:**  
Do not inhale explosion gases or combustion gases.  
Self-contained breathing apparatus.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected people away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure adequate ventilation at the workplace.  
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool, dry place.
- **Information about storage in one common storage facility:** Keep away from foodstuffs.
- **Further information about storage conditions:**  
Open containers carefully to prevent closure of the reaction with atmospheric moisture.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

GB

**Trade name: HADALAN FV 12P**

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**822-06-0 hexamethylene diisocyanate (< 2.5%)**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:** With good ventilation is not required.

· **Protection of hands:**

Protective gloves

Suitable materials: butyl rubber, nitrile, PVC

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	yellowish, transparent
<b>Odour:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

· **Flash point:** 160 °C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Density at 20 °C:** 1.14 g/cm<sup>3</sup>

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Solvent content:**

**Organic solvents:** 0.0 %

· **Other information** No further relevant information available.

GB

(Contd. on page 5)

**Trade name: HADALAN FV 12P**

(Contd. of page 4)

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Exothermic reactions with amines and alcohols. With water forming CO<sub>2</sub> - in closed containers, pressure build-up bursting.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

· **Information on toxicological effects**

Acute toxicity, by oral route:

Hexamethylene-1,6-diisocyanate homopolymer

LD50 rat: > 5000 mg / kg

Acute toxicity, by inhalation:

Hexamethylene-1,6-diisocyanate homopolymer:

LC50 rat, male: 543 mg / m<sup>3</sup>, 4 h

Method: OECD Test Guideline 403

LC50 rat, female: 390 mg / m<sup>3</sup>, 4 h

Method: OECD Test Guideline 403

The substance was tested in a form (ie, specific particle size distribution) which is of the forms as they are marketed and used in all probability, is different. On the basis of the "split-entry" concept and the available data on the particle size during the final application of the material, a modified classification of the acute inhalation toxicity is warranted.

Subacute, subchronic and prolonged toxicity:

Hexamethylene-1,6-diisocyanate homopolymer

Application Route: Subacute inhalation toxicity study, rat

Method: OECD Test Guideline 412

Test concentrations - 4.3, 14.7 and 89.8 mg aerosols / m<sup>3</sup>

Exposure time - 3 weeks (6 hours a day, 5 days per week)

4.3 mg / m<sup>3</sup> without compensation tolerated concentration (NOEL)

14.7 mg / m<sup>3</sup> increase in lung weight,

89.8 mg / m<sup>3</sup> inflammatory changes in the respiratory tract.

Links to other organ damage except to the respiratory systems were raised.

Genotoxicity in vitro:

Hexamethylene-1,6-diisocyanate homopolymer

Test Type: Salmonella / microsome test (Ames test)

Result: No evidence of mutagenic effects.

Method: OECD Test Guideline 471

Test Type: Chromosome aberration test in vitro

Result: negative

Method: OECD Test Guideline 473

Test Type: point mutation in mammalian cells (HPRT test)

Result: negative

Method: OECD Test Guideline 476

For more information:

Hexamethylene-1,6-diisocyanate homopolymer

Special Features / Effects: If over-exposure - especially when spraying isocyanate paints without protective measures, there is the risk of concentration-dependent irritation of eyes, nose, throat and respiratory tract.

Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may already be triggered at low isocyanate concentrations below the TLV value. By prolonged contact with skin tanning and irritating effects are possible. Animal

(Contd. on page 6)

**Trade name: HADALAN FV 12P**

(Contd. of page 5)

experiments and other studies indicate that skin contact with diisocyanates in isocyanate sensitization and respiratory reactions may play a role.

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** slightly irritating
- **on the eye:** slightly irritating
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

## 12 Ecological information

- **Toxicity**

Acute toxicity to fish:

Hexamethylene-1,6-diisocyanate homopolymer

LC50 > 100 mg / l

Species: *Danio rerio* (Zebrafish)

Exposure time: 96 h

Method: OECD Test Guideline 203

Sample preparation because of the reactivity of the substance with water:

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Acute Toxicity to daphnia:

Hexamethylene-1,6-diisocyanate homopolymer

EC50 > 100 mg / l

Species: *Daphnia magna* (water flea)

Exposure time: 48 h

Method: OECD Test Guideline 202

Sample preparation because of the reactivity of the substance with water:

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Acute Toxicity to algae:

Hexamethylene-1,6-diisocyanate homopolymer

IC50 > 100 mg / l

Tested to: *Scenedesmus subspicatus* Duration of test: 72 h

Method: OECD Test Guideline 201

Sample preparation because of the reactivity of the substance with water:

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Acute Toxicity to bacteria:

Hexamethylene-1,6-diisocyanate homopolymer

EC50 > 1000 mg / l

Tested on: activated sludge test time: 3 h

Method: OECD Test Guideline 209

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**

- **Bioaccumulative potential**

Hexamethylene-1,6-diisocyanate homopolymer

Biodegradation: 0%, 28 d, i.e. not readily biodegradable

Method: OECD Guideline 301 C

For more information on ecotoxicology:

The resin reacts with water at the interface to form carbon dioxide at a fixed, high-melting and insoluble reaction product (polyurea). This reaction is accelerated by surfactants (eg detergents) or water-soluble solvents.

Polyurea is inert Previous experience and non-degradable.

- **Mobility in soil** No further relevant information available.

(Contd. on page 7)



Printing date 04.07.2013

Revision: 04.07.2013

Trade name: **HADALAN FV 12P**

(Contd. of page 6)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Harmful to aquatic organisms  
Water hazard class: 1
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
  - **European waste catalogue**
- |           |   |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|-----------|---|
- **Uncleaned packaging:**
  - **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |                 |
|--|-----------------|
| · <b>UN-Number</b>   | Void            |
| · <b>ADR, IMDG, IATA</b>   | Void            |
| · <b>UN proper shipping name</b>   | Void            |
| · <b>ADR, IMDG, IATA</b>   | Void            |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>ADR, IMDG, IATA</b>   |                 |
| · <b>Class</b>   | Void            |
| · <b>Packing group</b>   |                 |
| · <b>ADR, IMDG, IATA</b>   | Void            |
| · <b>Environmental hazards:</b>  |                 |
| · <b>Marine pollutant:</b>   | No              |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
I	0.4

(Contd. on page 8)

Printing date 04.07.2013

Revision: 04.07.2013

Trade name: **HADALAN FV 12P**· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 7)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H315 Causes skin irritation.*
- H317 May cause an allergic skin reaction.*
- H319 Causes serious eye irritation.*
- H331 Toxic if inhaled.*
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H335 May cause respiratory irritation.*
- H412 Harmful to aquatic life with long lasting effects.*
- R23 Toxic by inhalation.*
- R36/37/38 Irritating to eyes, respiratory system and skin.*
- R42/43 May cause sensitisation by inhalation and skin contact.*
- R43 May cause sensitisation by skin contact.*
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: International Civil Aviation Organization*
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals*

GB