

Printing date 19.10.2012 Revision: 19.10.2012

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: HADALAN LF41 12E, Komp. A

· Article number: 50350 A

· Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the preparation

Solvent-free, 2 component, dispersion based epoxy resin coating for interior and exterior floor.

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Heinrich Hahne GmbH & Co. KG

Heinrich-Hahne-Weg 11

45711 Datteln

Tel.:02363/5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit

Tel.: 02363 5663-0

EMail: info@hahne-bautenschutz.de

· Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC
- · Hazard description: Xi Irritant
- · Information concerning particular hazards for human and environment:

R 41 Risk of serious damage to eyes.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

- · Risk phrases: 41 Risk of serious damage to eyes.
- · Safety phrases:

24/25 Avoid contact with skin and eyes.

- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37/39 Wear suitable gloves and eye/face protection.
- 46 If swallowed, seek medical advice immediately and show this container or label.

(Contd. on page 2)



Printing date 19.10.2012 Revision: 19.10.2012

Trade name: HADALAN LF41 12E, Komp. A

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

(Contd. of page 1)

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Compount of following substances with innocuous constituents.

· Dangerous co	· Dangerous components:		
260549-92-6	Polyamin-Addukt	<b>X</b> i R41	10 - 25%
		♦ Eye Dam. 1, H318	

#### 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air and to be sure call for a doctor.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam (alcohol resistant), carbon dioxide, powder, spray.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water jet.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: In case of fire: breathing protection with independent air supply.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Printing date 19.10.2012 Revision: 19.10.2012

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 2)

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in unopened original container.
- · Information about storage in one common storage facility:

Keep away from food, beverages and animal feedstocks

· Further information about storage conditions:

Store in cool, dry place.

Protect from frost.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

- · Respiratory protection: Not required if good ventilation.
- · Protection of hands:

Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Wear safety gloves made of nitrile rubber with a thickness < 0.4 mm (penetration time> 480 min - see also www.gisbau.de

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- $\cdot \textit{\textbf{Eye protection:}} \ Tightly \ sealed \ goggles$
- · Body protection: Protective clothing.

- CD



Printing date 19.10.2012 Revision: 19.10.2012

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 3)

#### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Boiling point/Boiling range: >100°C

· Flash point: Not applicable.

· Self-igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

• Density at 20 °C:  $1.65 \text{ g/cm}^3$ 

· Solubility in / Miscibility with

water: Fully miscible.

· Viscosity:

**Dynamic at 20°C:** 5000 mPas

• Other information No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 5)



Printing date 19.10.2012 Revision: 19.10.2012

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 4)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	-
UN proper shipping name	-
Transport hazard class(es)	-
Packing group	-
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.

#### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

For activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract regular preventive medical examinations must be initiated.

The product is subject to Directive 2004/42/EC.

EU limit value for the VOC content of this product in ready to use: cat A/j 140 g/l (2010).

The product contains a ready to use product: <5 g/l VOC.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB



Printing date 19.10.2012 Revision: 19.10.2012

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 5)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H318 Causes serious eye damage.

R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GR