

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** HADALAN PoolColor 12P, Komp. B
- **Article number:** 50352 A
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** 2-comp. colored pool paint based on polyurethane dispersion.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Heinrich Hahne GmbH & Co. KG
Heinrich-Hahne-Weg 11
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**
Abteilung: Produktsicherheit
Tel.: 02363 5663-0
EMail: info@hahne-bautenschutz.de
- **Emergency telephone number:**
Gif tinformationszentrum Nord (GIZ Nord) Universität Göttingen,
Tel.: 0551-19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
- **Hazard description:** Xi Irritant
- **Information concerning particular hazards for human and environment:**
R 43 May cause sensitisation by skin contact.
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Contains isocyanates. May produce an allergic reaction.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning

(Contd. on page 2)

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 1)

· **Hazard-determining components of labelling:**

Hydrophiles, aliphatisches Polyisocyanat
hexamethylene diisocyanate

· **Hazard statements**

H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.







· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Paint component B, aliphatic polyisocyanate

· **Dangerous components:**

CAS: 822-06-0	hexamethylene diisocyanate	< 0.5%
EINECS: 212-485-8	 T R23;  Xn R42/43;  Xi R36/37/38  Acute Tox. 3, H331;  Resp. Sens. 1, H334;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	

· **Additional information:**

For the wording of the listed risk phrases refer to section 16.
GISCODE: PU 40 (Part A + B).

4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 3)

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 2)

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Extinguishing Media: CO₂, foam, dry powder, water spray for large fires.
- **Special hazards arising from the substance or mixture**
In case of fire carbon monoxide, nitrogen oxides, isocyanate vapors and traces of hydrogen cyanide may arise.
- **Advice for firefighters**
- **Protective equipment:**
When extinguishing fires, use breathing apparatus with independent air supply.
Contaminated water can not penetrate into the soil, groundwater and surface waters.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation / exhaust. Evacuate all personnel.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Take up mechanically, cover remainders with wet absorbent material (sawdust, chemical binder, sand). After 1 hour transfer to waste container record, no cover (CO₂ evolution). Keep damp in a safe ventilated in Freuien several days. other disposal see chapter 13
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure adequate ventilation / exhaust. Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Keep container tightly closed in a cool, well-ventilated place.
- **Information about storage in one common storage facility:** Do not store together with food.
- **Further information about storage conditions:**
Store in dry conditions.
Protect from frost.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

GB

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

822-06-0 hexamethylene diisocyanate (< 0.5%)

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:** If good ventilation is not required.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: colorless

· **Odour:** almost odorless

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 300 °C

· **Flash point:** 184 °C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Density at 20 °C:** 1.15 g/cm³

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

Dynamic at 20 °C: 1400 mPas

(Contd. on page 5)

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 4)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Exothermic reactions with amines and alcohols with water gradual development of CO₂, in closed containers, pressure build-up and burst.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

822-06-0 hexamethylene diisocyanate

Oral	LD50	746 mg/kg (rat)
Dermal	LD50	599 mg/kg (rab)

- **Specific symptoms in biological assay:**

Below are the available toxicological data on components.

Acute toxicity, by oral route:

Aliphatic polyisocyanate LD50 rat: > 2000 mg / kg

Hexamethylene-1,6-diisocyanate homopolymer LD50 rat: > 5000 mg / kg

Acute toxicity, by inhalation:

Hexamethylene-1,6-diisocyanate homopolymer rat LC50: 158 mg / l, 4 h

Method: OECD Test Guideline 403

Hexamethylene-1,6-diisocyanate rat LC50: 0.124 mg / l, 4 h

Concentration of the saturated vapor of 1,6-HDI at 25 °C: 0.095 mg / l

Primary skin irritation:

Aliphatic polyisocyanate rabbit Result: slightly irritating

Hexamethylene-1,6-diisocyanate homopolymer rabbit Result: slightly irritating

Method: OECD Test Guideline 404

Hexamethylene-1,6-diisocyanate rabbit Result: strong irritant

Primary eye irritation:

Aliphatic polyisocyanate rabbit Result: slightly irritating

Hexamethylene-1,6-diisocyanate homopolymer rabbit Result: slightly irritating

Method: OECD Test Guideline 405

Hexamethylene-1,6-diisocyanate rabbit Result: strong irritant

- **Primary irritant effect:**

- **on the skin:** slightly irritating

- **on the eye:** slightly irritating

- **Sensitization:** Sensitization possible through skin contact.

- **Other information (about experimental toxicology):**

sensitization:

aliphatic polyisocyanate

Skin sensitization according to Magnusson / Kligman (maximization test): guinea pig

Result: positive

Method: OECD Test Guideline 406

Hexamethylene-1,6-diisocyanate homopolymer

Skin sensitization according to Magnusson / Kligman (maximization test): guinea pig

(Contd. on page 6)

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 5)

Result: The product acts on guinea pig sensitization.

Method: OECD Test Guideline 406

No pulmonary sensitization in animal studies.

Both after intradermal as well as inhalational induction was observed with polyisocyanate based on hexamethylene diisocyanate in guinea pigs no lungensensibilisierendes potential.

Hexamethylene-1,6-diisocyanate

Skin sensitization according to Magnusson / Kligman (maximization test): guinea pig

Result: positive

Method: OECD Test Guideline 406

Genotoxicity in vitro:

Aliphatic polyisocyanate Ames test Result: negative

Method: OECD Test Guideline 471

Toxicological studies of a comparable product.

Hexamethylene-1,6-diisocyanate homopolymer Ames test Result: negative

Method: OECD Test Guideline 471

Hexamethylene-1,6-diisocyanate

Salmonella / microsome test (Ames test): Result: negative

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· Repeated dose toxicity

Over-exposure risk of concentration-dependent irritation is on the eyes, nose, throat and respiratory tract.

Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may already be triggered at low isocyanate concentrations below the TLV value. By prolonged contact with skin tanning and irritating effects are möglich. Tierversuche and other studies indicate that skin contact with diisocyanates in isocyanate sensitization and respiratory reactions may play a role.

12 Ecological information

· Toxicity

· Aquatic toxicity: *No further relevant information available.*

· Persistence and degradability *No further relevant information available.*

· Other information:

Toxicity to fish:

aliphatic polyisocyanate

LC50 28.3 mg / l

Test Species: Brachydanio rerio (zebra fish) Duration of test: 96 h

Method: OECD Test Guideline 203

Hexamethylene-1,6-diisocyanate

LC0> 82.8 mg / l

Test Species: Brachydanio rerio (zebra fish) Duration of test: 96 h

Method: OECD Test Guideline 203

Sample preparation because of the reactivity of the substance with water:

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Acute Toxicity to daphnia:

aliphatic polyisocyanate

EC50> 100 mg / l

Test species: Daphnia magna (water flea) Duration of test: 48 h

Method: OECD Test Guideline 202

Sample preparation because of the reactivity of the substance with water:

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Hexamethylene-1,6-diisocyanate

EC0> 89.1 mg / l

Test species: Daphnia magna (water flea) Duration of test: 48 h

Sample preparation because of the reactivity of the substance with water:

(Contd. on page 7)

Trade name: HADALAN PoolColor 12P, Komp. B

(Contd. of page 6)

Ultra turrax: 60 sec 8000 rpm, 24 magnetic stirrer; filtration.

Acute Toxicity to bacteria:

aliphatic polyisocyanate

EC50 > 10,000 mg / l

Method: OECD Test Guideline 209

Hexamethylene-1,6-diisocyanate

EC50 842 mg / l

Tested on: activated sludge test time: 3 h

Method: OECD Guideline for Testing of Chemicals, No.209

Acute Toxicity to algae:

aliphatic polyisocyanate

IC50 > 100 mg / l

Tested to: *Scenedesmus subspicatus* Duration of test: 72 h

Method: OECD Test Guideline 201

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Other information:**

The resin reacts with water at the interface to form carbon dioxide at a fixed, high-melting and insoluble reaction product (polyurea). This reaction is accelerated by surfactants (eg detergents) or water-soluble solvents. Polyurea is inert Previous experience and non-degradable.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **IMDG, IATA**

Void

· **UN proper shipping name**

· **IMDG, IATA**

Void

· **Transport hazard class(es)**

· **IMDG, IATA**

· **Class**

Void

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.09.2014

Revision: 29.09.2014

Trade name: **HADALAN PoolColor 12P, Komp. B**

(Contd. of page 7)

· Packing group · IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not classified as dangerous.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
I	0.1

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Other regulations, limitations and prohibitive regulations**
This product is subject to Directive 2004/42/EC.
EU limit value for the VOC content of this product is ready for use: 140 g / l (2007), 140 g / l (2010).
The product contains a ready to use product: <10 g / l VOC.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.

R23 Toxic by inhalation.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitisation by inhalation and skin contact.

- **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent