Printing date 05.10.2018

	NO REVISION. 05.10.2010
SECTION 1: 1	dentification of the substance/mixture and of the company/undertaking
· 1.1 Product ident	ifier
• Trade name: <u>HA</u>	DALAN SBH 13E, Komp. B
• Article number: 5 • 1.2 Relevant iden No further relevant	
• 1.3 Details of the • Manufacturer/Su Heinrich Hahne (Heinrich-Hahne- D-45711 Datteln Tel.: +49 2363 50	GmbH & Co. KG Weg 11
Abteilung: Produ. Tel.: 02363 5663 EMail: info@hah • 1.4 Emergency te	-0 ne-bautenschutz.de
SECTION 2: 1	Hazards identification
Classification acc	of the substance or mixture cording to Regulation (EC) No 1272/2008 corrosion H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
	environmeni
Aquatic Chronic 2	2 H411 Toxic to aquatic life with long lasting effects.
Skin Sens. 1	H317 May cause an allergic skin reaction.
	ing to Regulation (EC) No 1272/2008 ussified and labelled according to the CLP regulation.
GHS05 GHS0	7 GHS09
· Signal word Dang	ger

(Contd. on page 2) _____ GB ____

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

	(Contd. of page
· Hazard statem	ents
H314 Causes s	evere skin burns and eye damage.
H317 May cau	se an allergic skin reaction.
•	aquatic life with long lasting effects.
· Precautionary	
P260	Do not breathe mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P	2353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin was water/shower.
P305+P351+P	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
· 2.3 Other haza	rds
· Results of PBT	and vPvB assessment
• PBT: Not appl	
• vPvB: Not app	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Amine-containing curing agents for epoxy resins.

· Dangerous compone	nts:	
CAS: 2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
EINECS: 220-666-8	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 1477-55-0	m-phenylenebis(methylamine)	10-25%
EINECS: 216-032-5	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 61788-44-1	phenol, styrenated	25-50%
	𝔅 Aquatic Chronic 2, H411; 𝔅 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 69-72-7	Salicylic acid	<2.5%
EINECS: 200-712-3	() Acute Tox. 4, H302	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- $\cdot \textit{After skin contact: Immediately wash with water and so ap and rinse thoroughly.}$
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Foam (alcohol resistant), carbon dioxide, dry chemical, dry sand, limestone powder.
- · For safety reasons unsuitable extinguishing agents: Water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:

Avoid contact with skin. Face protection. Use personal protective equipment. In case of fire, if necessary, wear self-contained breathing apparatus.

· Additional information

Run-off water from getting into sewage or water courses of fire fighting.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. • Information about fire - and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in original container.
- Information about storage in one common storage facility: Do not store together with acids.
- Store away from foodstuffs, beverages and feed.
- · Further information about storage conditions: Protect from frost.
- Storage class: VCI: 8
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• DNELs salicylic acid Workers, skin: long-term - systemic effects 2 mg / kg

(Contd. on page 4)

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

	(Contd. of page 3)
Worker, Skin: Systemic effects	(00000000) F18000)
Workers, inhalation: long-term systemic effects 16 mg / m3	
Workers, Inhalation: Systemic effects 16 mg / m3	
Consumers, Oral: Acute - systemic effects 4 mg / kg	
Consumers, Oral: Systemic Effects	
Consumers, skin: long-term systemic effects 1 mg / kg	
Consumer, Skin: Systemic effects	
Consumers, Inhalation: Long - term systemic effects: 4 mg / m3	
Consumers, Inhalation: Systemic effects 4 mg / m3	
Consumers, Oral: Long-term - systemic effects: 1 mg / kg	
Consumers, Oral: Systemic Effects Consumers, Inhalation: Long-term - local effects 0.2 mg / m3	
Consumers, Inhalation: Local effects 0.2 mg / m3	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Workers, Inhalation: systemic effects, short-term exposure 20.1 mg / m3	
Workers, Inhalation: Local effects, short-term exposure 20.1 mg/m3	
Consumers, Oral: systemic effects, long-term exposure 0.526 mg / kg bw / day	
· PNECs	
salicylic acid	
Fresh water 0.2 mg / l	
Seawater 0.02 mg / l	
Fresh water - temporarily 1 mg / l	
Sewage treatment plant 162 mg / l	
Fresh water sediment 1.42 mg / kg	
Marine sediment 0.142 mg / kg	
Soil 0.166 mg / kg	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Fresh water 0.06 mg /l	
Seawater 0.006 mg / l Freshwater - at times 0.23 mg / l	
Sewage treatment plant 3.18 mg / l	
Freshwater sediment 5.784 mg / l	
Marine sediment 0.578 mg / kg	
Soil 1.121 mg / kg	
• Additional information: The lists valid during the making were used as basis.	
• • •	
· 8.2 Exposure controls · Personal protective equipment:	
· General protective equipment.	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes and skin.	
· Respiratory protection:	
Not required with good ventilation. At insufficiently ventilated workplaces and at the Spra	y treatment Apply
respiratory protection. Filter A / P	
· Protection of hands:	
Protective gloves	
The glove material has to be impermeable and resistant to the product/ the substance/ the product/	
Selection of the glove material on consideration of the penetration times, rates of a	diffusion and the
degradation	
Protective nitrile gloves with a layer thickness of at least 0.4 mm reagen (penetrating > 4	480 Min. See also
www.gisbau.de).	
• Material of gloves	mark f - 1.
The selection of the suitable gloves does not only depend on the material, but also on furthe and varies from manufacturer to manufacturer. As the product is a preparation of sever	
resistance of the glove material can not be calculated in advance and has therefore to be ch	
application.	iecheu prior io ine
иррисанон.	(Contd. on page 5)

(Contd. on page 5) GB

Printing date 05.10.2018

Revision: 05.10.2018

(Contd. of page 4)

Trade name: HADALAN SBH 13E, Komp. B

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles

· Body protection: Impervious clothing.

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	liquid
Colour:	yellowish
Odour:	by amine
Odour threshold:	Not determined.
pH-value at 20 °C:	>7
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 265 °C
Flash point:	110 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Vapour pressure:	Not determined.
Density at 20 °C:	1 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	miscible
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	600 mPas
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Keep away from strongly acidic and alkaline materials as well as oxidizing agents, to avoid exothermic reaction.

· 10.3 Possibility of hazardous reactions

In the case of heating, formation of carbon monoxide, carbon dioxide, nitrogen oxides, ammonia, aldehyde, flammable hydrocarbon fragments possible.

(Contd. on page 6)

- GB -

Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.10.2018

Revision: 05.10.2018

(Contd. of page 5)

Trade name: HADALAN SBH 13E, Komp. B

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects Acute oral toxicity - Product: *LD50 (rat):*> 2,000 mg / kg Method: The following toxicological data were obtained from tests of products of similar composition accepted. Acute inhalation toxicity - Product: Acute toxicity estimate:> 5 mg / l Exposure time: 4 h Test atmosphere: dust / mist Method: Calculation method Acute dermal toxicity - Product: Acute toxicity estimate:> 2,000 mg / kg Method: Calculation method · Acute toxicity Based on available data, the classification criteria are not met. · Primary irritant effect: · Skin corrosion/irritation Causes severe skin burns and eye damage. · Serious eye damage/irritation Causes serious eye damage. · Respiratory or skin sensitisation May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Must not reach sewage water or drainage ditch undiluted or unneutralised. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GB

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	UN3267
ADR, IMDG, IATA	01\\3207
14.2 UN proper shipping name	
ADR	3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S
	(ISOPHORONEDIAMINE, m-phenylenebis(methylamine) ENVIRONMENTALLY HAZARDOUS
IMDG	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S
	(ISOPHORONEDIAMINE, m-phenylenebis(methylamine)
	MARINE POLLUTANT
IATA	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S
	(ISOPHORONEDIAMINE, m-phenylenebis(methylamine))
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	8 Corrosive substances.
Label	8
IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group	
ADR, IMDĞ, IATA	Ι
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	88 E 4 6 D
EMS Number:	F-A,S-B
Segregation groups	Alkalis
14.7 Transport in bulk according to Anna Margal and the IBC Code	
Marpol and the IBC Code	Not applicable.

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

	(Contd. of page 7)
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	0
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	1
• Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities ($\widetilde{E}Q$)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC,
5	N.O.S. (ISOPHORONEDIAMINE, M-
	PHENYLENEBIS(METHYLAMINE)), 8, I,
	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

- · Other regulations, limitations and prohibitive regulations
- **VOC (EU)** 0.0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)

GB

Printing date 05.10.2018

Revision: 05.10.2018

Trade name: HADALAN SBH 13E, Komp. B

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1	(Contd. of page 8)
	CP -