

Printing date 22.07.2013

Revision: 22.07.2013

Identification	n of the substance/mixture and of the company/u	ıdertaking
Product identifi	ier	
Trade name: <u>H</u>	ADALAN VS 12E, Komp.A	
No further relevent Application of the second secon	: 50109 B fied uses of the substance or mixture and uses advised again vant information available. the substance / the preparation o component epoxy resin floor coating with good resistance	
Manufacturer/S	e GmbH & Co. KG	Tel.:02363/5663
Abteilung: Prod Tel.: 02363 566 EMail: info@ha <b>Emergency tele</b>	53-0 ahne-bautenschutz.de <b>phone number:</b> szentrum Nord (GIZ Nord) Universität Göttingen,	
Hazards iden Classification o	ttification f the substance or mixture	
Сня	according to Regulation (EC) No 1272/2008	
$\checkmark$	09 environment c 2 H411 Toxic to aquatic life with long lasting effects.	
Aquatic Chronic	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07	
Aquatic Chronic GHSC Skin Irrit. 2	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation.	
Aquatic Chronic Aquatic Chronic GHSC Skin Irrit. 2 Eye Irrit. 2	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation. H319 Causes serious eye irritation.	
Aquatic Chronic Aquatic Chronic GHSC Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification at Hazard descript Xi Irritant	<ul> <li>09 environment</li> <li>c 2 H411 Toxic to aquatic life with long lasting effects.</li> <li>07</li> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>Eccording to Directive 67/548/EEC or Directive 1999/45/EC</li> <li>tion:</li> </ul>	
Aquatic Chronic Aquatic Chronic Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification at Hazard descript Xi Irritant N Dangerous for Information con R 36/38 Irritan	<ul> <li>09 environment</li> <li>c 2 H411 Toxic to aquatic life with long lasting effects.</li> <li>07</li> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>Eccording to Directive 67/548/EEC or Directive 1999/45/EC tion:</li> <li>For the environment</li> <li>ncerning particular hazards for human and environment: ting to eyes and skin.</li> </ul>	
Aquatic Chronic Aquatic Chronic Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification a Hazard descript Xi Irritant N Dangerous fo Information con R 36/38 Irritan R 43 May ca R 51/53 Toxic effects in	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. <b>Excording to Directive 67/548/EEC or Directive 1999/45/EC</b> tion: for the environment <b>ncerning particular hazards for human and environment:</b> ting to eyes and skin. ause sensitisation by skin contact. to aquatic organisms, may cause long-term adverse the aquatic environment.	
Aquatic Chronic Aquatic Chronic GHSC Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification and Hazard descript Xi Irritant N Dangerous for Information con R 36/38 Irritant R 43 May can R 43 May can R 51/53 Toxic effects in Contains epoxy Classification sy The classification	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Cocording to Directive 67/548/EEC or Directive 1999/45/EC tion: for the environment ncerning particular hazards for human and environment: ting to eyes and skin. ause sensitisation by skin contact. to aquatic organisms, may cause long-term adverse the aquatic environment. constituents. May produce an allergic reaction.	
Aquatic Chronic Aquatic Chronic GHSC Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification at Hazard descript Xi Irritant N Dangerous for Information con R 36/38 Irritan R 43 May ca R 51/53 Toxic effects in Contains epoxy Classification sy	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Cccording to Directive 67/548/EEC or Directive 1999/45/EC tion: or the environment ncerning particular hazards for human and environment: ting to eyes and skin. ause sensitisation by skin contact. to aquatic organisms, may cause long-term adverse the aquatic environment. constituents. May produce an allergic reaction. ystem:	
Aquatic Chronic Aquatic Chronic GHSC Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 Classification and Hazard descript Xi Irritant N Dangerous for Information con R 36/38 Irritan R 43 May can R 43 May can R 51/53 Toxic effects in Contains epoxy Classification sy The classification sy The classification data. Label elements Labelling accor	09 environment c 2 H411 Toxic to aquatic life with long lasting effects. 07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Cccording to Directive 67/548/EEC or Directive 1999/45/EC tion: or the environment ncerning particular hazards for human and environment: ting to eyes and skin. ause sensitisation by skin contact. to aquatic organisms, may cause long-term adverse the aquatic environment. constituents. May produce an allergic reaction. ystem:	tended by company and literati

Printing date 22.07.2013

Revision: 22.07.2013

hahne

Bautenschutz Systeme

Trade name: HADALAN VS 12E, Komp.A

GISCODE: RE 1 (resin + hardener)	(Contd. of page 1
Code letter and hazard designation of product:	
Xi Irritant N Dangerous for the environment	
Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecul Bisphenol-F Epichlorhydrinharz Reaktionspr.Phenol-Formaldehyd Novolak mit Epic oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
<ul> <li>Risk phrases:</li> <li>36/38 Irritating to eyes and skin.</li> <li>43 May cause sensitisation by skin contact.</li> <li>51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> </ul>	
<ul> <li>Safety phrases:</li> <li>24/25 Avoid contact with skin and eyes.</li> <li>26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>27 Take off immediately all contaminated clothing.</li> <li>29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.</li> <li>36/37/39 Wear suitable protective clothing, gloves and eye/face protection.</li> <li>45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).</li> </ul>	
Special labelling of certain preparations: Contains epoxy constituents. May cause al Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.	lergic reactions.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions

· Dangerous	components:
-------------	-------------

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number	>25- <40%
NLP: 500-033-5	average molecular weight = $700$ )	
	🗙 Xi R36/38; 🗙 Xi R43; 🏪 N R51/53	
	Aquatic Chronic 2, H411; () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 28064-14-4	Bisphenol-F Epichlorhydrinharz Reaktionspr. Phenol-Formaldehyd	>5 - <10%
	Novolak mit Epichlorhydrin	
	🗙 Xi R36/38; 🗙 Xi R43; 🏪 N R51/53	
	Aquatic Chronic 2, H411; () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	>5 - <10%
EINECS: 271-846-8	🗙 Xi R38; 🗙 Xi R43	
	🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317	
		Contd. on page

Printing date 22.07.2013



Revision: 22.07.2013

Trade name: HADALAN VS 12E, Komp.A

• Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. of page 2)

### 4 First aid measures

- · Description of first aid measures
- · General information: Remove contaminated clothing immediately.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- *Use fire extinguishing methods suitable to surrounding conditions. Foam (alcohol resistant), carbon dioxide, powder, spray*
- · For safety reasons unsuitable extinguishing agents: Water jet.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: In case of fire: Use breathing apparatus with independent air supply.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Keep people away, provide adequate ventilation.
- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# 7 Handling and storage

#### · Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Prevent formation of aerosols.
   Store in tightly closed containers in a cool, dry place.
- · Information about fire and explosion protection: No special measures required.

(Contd. on page 4)

Printing date 22.07.2013

hahne Bautenschutz Systeme

Revision: 22.07.2013

Trade name: HADALAN VS 12E, Komp.A

(Contd. of page 3)

GB

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles: Keep container in a cool, well-ventilated place.*
- Information about storage in one common storage facility: Store away from foodstuffs, beverages and feed.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: VCI: 10
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection: If good ventilation is not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Nitrile gloves with a thickness of > 0,4 mm wear (breakthrough time 480 min <sup>3</sup>-see also www.gisbau.de)  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles

### 9 Physical and chemical properties

• Information on basic • General Information	physical and chemical properties	
· Appearance:		
Form:	Fluid	
Colour:	according to product specification	
Odour:	Characteristic	
pH-value:	n.a.	
Change in condition		
Melting point/Melti	ng range: Undetermined.	
Boiling point/Boilin		
		(Contd. on page



Revision: 22.07.2013

Printing date 22.07.2013

#### Trade name: HADALAN VS 12E, Komp.A

		(Contd. of page 4
· Flash point:	140 °C	
· Ignition temperature:	450 °C	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
• Density at 20 °C:	1.6 g/cm <sup>3</sup>	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
• Viscosity: Dynamic at 20 °C:	9500 mPas	
· Solvent content:		
Organic solvents:	0.0 %	
• Other information	No further relevant information available.	

# **10 Stability and reactivity**

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Exothermic reactions with amines. Processed quickly after adding the hardener, since in the high curing temperatures can be achieved.

- · Conditions to avoid No further relevant information available.
- Incompatible materials: From highly acidic or alkaline materials as well as oxidiz
- From highly acidic or alkaline materials as well as oxidizers away to avoid exothermic reactions.
- Hazardous decomposition products:

At high temperatures, carbon monoxide and dioxide, smoke and oxides of nitrogen.

# 11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

# **12** Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
   Mobility in soil No further relevant information available.

(Contd. on page 6)

<sup>—</sup> GB



Printing date 22.07.2013

Revision: 22.07.2013

### Trade name: HADALAN VS 12E, Komp.A

(Contd. of page 5)

- · Ecotoxical effects:
- Remark: Toxic for fish
- $\cdot$  Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

· Waste treatment methods

· Recommendation


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 $\cdot$  European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

· UN-Number · ADR, IMDG, IATA	3082
· UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecular weigh = 700))
· IMDG, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S.
• Transport hazard class(es)	
ADR	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9



Revision: 22.07.2013

Trade name: HADALAN VS 12E, Komp.A

	(Contd. of page
·IMDG	
· Class	9 Miscellaneous dangerous substances and articles.
· Class	9 Miscellaneous dangerous substances and articles.
· Packing group · ADR	III
<ul> <li>Environmental hazards:</li> <li>Marine pollutant:</li> <li>Special marking (ADR):</li> <li>Special marking (IATA):</li> </ul>	No Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler):	Warning: Miscellaneous dangerous substances and articles. 90
• Transport in bulk according to Annex . MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	LQ7 3 E
· UN "Model Regulation":	UN3082, 3082 UMWELTGEFÄHRDENDER STOFF, FLÜSSIG N.A.G. (Reaktionsprodukt: Bisphenol-A-Epichlorhydrinharz mit durchschnittlichem Molekulargewicht ≤700), 9, III

# **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture


- · National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Other regulations, limitations and prohibitive regulations For activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract regular preventive medical examinations are to be taken.
- $\cdot V OC (EU)$

The product is subject RL 2004/42/EG.EU-Grenzwert this product is used in the manufacture condition: Cat A / j max. 500 g / l (2010). The product contains used in the finished state: max. 150 g / l VOC. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

GB





Bautenschutz Systeme *Revision: 22.07.2013* 

hahne

# Trade name: HADALAN VS 12E, Komp.A

(Contd. of page 7)

GB

	<mark>r information</mark> Iformation is based on our present knowledge. However, this shall not constitute a guarantee for
	c product features and shall not establish a legally valid contractual relationship.
Releva	unt phrases
	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
	8 Irritating to eyes and skin.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
	3 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	viations and acronyms:
RID: Rè	glement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concernin
	ional Transport of Dangerous Goods by Rail)
	GR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) nternational Civil Aviation Organization
	I: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
	ccord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internat
	e of Dangerous Goods by Road)
	International Maritime Code for Dangerous Goods nternational Air Transport Association
	lobally Harmonized System of Classification and Labelling of Chemicals