

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** HADALAN VS 12E, Komp. B
- **Article number:** 50044 B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Solvent-free, two component epoxy resin floor coating with good resistance to mechanical and chemical loads
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Heinrich Hahne GmbH & Co. KG
Heinrich-Hahne-Weg 11
45711 Datteln Tel.: 02363/5663-0
- **Further information obtainable from:**
Abteilung: Produktsicherheit
Tel.: 02363 5663-0
Email: info@hahne-bautenschutz.de
- **1.4 Emergency telephone number:**
Gif tinformati onszentrum Nord (GIZ Nord) Universität Göttingen,
Tel.: 0551-19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
- **Hazard description:** C Corrosive
- **Information concerning particular hazards for human and environment:**
R 34 Causes burns.
R 43 May cause sensitisation by skin contact.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05



GHS07

Trade name: HADALAN VS 12E, Komp. B





(Contd. of page 1)

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated
- **Hazard statements**
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
- **Precautionary statements**
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P262 Do not get in eyes, on skin, or on clothing.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** *Amine-containing curing agents for epoxy resins.*

- **Dangerous components:**

1173092-74-4	Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	>25%
	 C R34;  Xi R43  Skin Corr. 1B, H314;  Skin Sens. 1, H317	

- **Additional information:**
For the wording of the listed risk phrases refer to section 16.
GISCODE: RE 1 (Part A + B)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*
- **After swallowing:**
Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **4.3 Indication of any immediate medical attention and special treatment needed**
NOTE TO PHYSICIANS: Application of corticosteroid cream has been shown to be effective in the treatment of skin irritation.

GB

(Contd. on page 3)

Trade name: HADALAN VS 12E, Komp. B

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Foam (alcohol resistant), carbon dioxide, dry chemical, dry sand, limestone powder.
- **5.2 Special hazards arising from the substance or mixture**
Incomplete combustion carbon monoxide may arise. May evolve ammonia gas. May evolve toxic nitrogen oxides. Burning produces obnoxious and toxic fumes. personnel in wind direction has to be evacuated.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear suitable respiratory equipment.
Avoid contact with skin. Face protection. Use personal protective equipment. In case of fire, if necessary, wear self-contained breathing apparatus.
- **Additional information**
Run-off water from getting into sewage or water courses of fire fighting.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Store in a cool, dry place.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in original container.
- **Information about storage in one common storage facility:**
Do not store together with acids.
Store away from foodstuffs, beverages and feed.
- **Further information about storage conditions:** Protect from frost.
- **Storage class:** VCI: 8

(Contd. on page 4)

Trade name: HADALAN VS 12E, Komp. B

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
If good ventilation is not required. In inadequately ventilated places and during spray processing, wear respiratory protection. A/P2 filter.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Protective gloves made of nitrile with a layer thickness of at least 0.4 mm reagen (breakthrough time > 480 min see also www.gisbau.de).
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed goggles
- **Body protection:** Impervious clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	liquid
Colour:	yellowish
Odour:	by amine.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	205 °C
- **Flash point:** 101 °C
- **Ignition temperature:** 435 °C
- **Self-igniting:** Product is not selfigniting.

(Contd. on page 5)

Trade name: HADALAN VS 12E, Komp. B

(Contd. of page 4)

- | | |
|--|---|
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Vapour pressure at 50 °C: | <5 hPa |
| · Density at 20 °C: | 1.0 g/cm ³ |
| · Solubility in / Miscibility with water: | miscible |
| · Solvent content: | |
| · Organic solvents: | 0.0 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Prior to strongly acidic and alkaline materials as well as oxidants in order to avoid exothermic reactions.
- **10.6 Hazardous decomposition products:** Possible at > 60 °C elimination of acrylonitrile.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitisation:** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)

Printing date 27.05.2015

Revision: 27.05.2015

Trade name: HADALAN VS 12E, Komp. B

(Contd. of page 5)

Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN2735 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)
AMINES, LIQUID, CORROSIVE, N.O.S. (Polyamine) |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 8 Corrosive substances.
8 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | III |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups | Warning: Corrosive substances.
80
F-A,S-B
Alkalis |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 7)

Trade name: HADALAN VS 12E, Komp. B

(Contd. of page 6)

· Transport/Additional information:

· ADR

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- **Transport category**
- **Tunnel restriction code**

3
E

· IMDG

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE), 8, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· Other regulations, limitations and prohibitive regulations

For activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract regular checkups are causing.

VOC (EU):

This product is subject to Directive 2004/42 / EG.EU limit for this product is used in the finished state: Kat A / j max. 500 g / l (2010). The product contains hand finished state: max. 150 g / l VOC.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.05.2015

Revision: 27.05.2015

Trade name: HADALAN VS 12E, Komp. B

CAS: Chemical Abstracts Service (division of the American Chemical Society)
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

(Contd. of page 7)

GB