

**DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011  
for the product

**INTRASIT<sup>®</sup> Poly-C1 54Z**

**Nr. 1037434**

---

1. Unique identification code of the product-type:

**EN 14891 CM**

---

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**batch number: see packaging of the product**

---

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**2-komponent coating with polymer modified cement  
for alternative sealings**

---

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Heinrich Hahne GmbH & Co.KG  
Heinrich-Hahne-Weg 11  
D - 45711 Datteln**

---

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**not relevant**

---

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

---

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The notified body MPA-Dortmund, identification number 0432, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No. 220010065-13**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**not relevant**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Bond strenght (at beginning)	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Bond strenght after contact with water	$\geq 0,5 \text{ N/mm}^2$	
Bond strenght after aging by heat	$\geq 0,5 \text{ N/mm}^2$	
Bond strength after frost – dew demands	$\geq 0,5 \text{ N/mm}^2$	
Bond strength after contact with chalk-water	$\geq 0,5 \text{ N/mm}^2$	
Watertightness	no leak	
Crack-bridging ability	$\geq 0,75 \text{ mm}$	
Dangerous substances	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:  
Michael Horstmann / Technician

Datteln, 25.06.2013.....



(signature)

### Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance.