

Printing date 23.05.2013 Revision: 23.05.2013

I Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: INTRASIT FSM 55Z

· Article number: 50114 B

· Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the preparation

Polymer-modified special mortar giving early-strength, INTRASIT® FSM Winter 56Z is suitable even for temperatures down to -5 °C.

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Heinrich Hahne GmbH & Co. KG

Heinrich-Hahne-Weg 11

45711 Datteln

Tel.:02363/5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit

Tel.: 02363 5663-0

EMail: in fo@hahne-bautenschutz.de

· Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi Irritant
- · Information concerning particular hazards for human and environment:

R 37/38 Irritating to respiratory system and skin.

R 41 Risk of serious damage to eyes.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

GISCODE: ZP 1

(Contd. on page 2)



Printing date 23.05.2013 Revision: 23.05.2013

Trade name: INTRASIT FSM 55Z

(Contd. of page 1)

· Code letter and hazard designation of product:



Xi Irritant

· Risk phrases:

37/38 Irritating to respiratory system and skin.

41 Risk of serious damage to eyes.

· Safety phrases:

22 Do not breathe dust.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · After inhalation:

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Not applicable, product is not flammable.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)



Printing date 23.05.2013 Revision: 23.05.2013

Trade name: INTRASIT FSM 55Z

(Contd. of page 2)

· Additional information Product hardens on contact with water.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Avoid formation of dust.
- · Environmental precautions: Do not empty into drains / surface water / ground water.
- · Methods and material for containment and cleaning up: Pick up mechanically.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Avoid formation of dust.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Only in unopened original container.
- Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions: Store in dry conditions.
- · Storage class: Storage category: 13 Non-hazardous solid brand.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals (25-50%)

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use a dust mask if dust is generated.

Dust mask P1.

Leaflet ZH 1/134 BG

· Protection of hands:

Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)



Printing date 23.05.2013 Revision: 23.05.2013

Trade name: INTRASIT FSM 55Z

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: In case of dust or splashes goggles.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid
Colour: Grey
Odourless

• pH-value (100 g/l) at 20 °C: 11-13

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

· Flash point: Not applicable.

· Self-igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Density: Not determined.

· Solubility in / Miscibility with

water: dispersible

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization:

As long as the expiration date of the product is not exceeded, a sensitizing effect is not expected.

(Contd. on page 5)



Printing date 23.05.2013 Revision: 23.05.2013

Trade name: INTRASIT FSM 55Z

(Contd. of page 4)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot \textit{Mobility in soil No further relevant information available}.$
- · Additional ecological information:
- · General notes: Class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

17 01 01 | concrete

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

· UN-Number	-
· UN proper shipping name	-
· Transport hazard class(es)	-
· Packing group	-
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	not a dangerous good under transport regulations

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to EU guidelines:
- · Hazard-determining components of labelling: Portland cement

(Contd. on page 6)



Printing date 23.05.2013 Revision: 23.05.2013

Trade name: INTRASIT FSM 55Z

(Contd. of page 5)

- · National regulations:
- · Waterhazard class: Class 1 (Self-assessment): slightly hazardous for water
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GB ·