

Printing date 19.10.2012 Revision: 18.10.2012

## 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: INTRASIT Poly-C1 54Z, powder

· Article number: 50195 B

· Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the preparation

Hairline crack-bridging, two-component coating compound for alternative damp-proofing with layer thicknesses from 1.5 to 5 mm.

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Heinrich Hahne GmbH & Co. KG

Heinrich-Hahne-Weg 11

45711 Datteln

Tel.:02363/5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit

Tel.: 02363 5663-0

EMail: in fo@hahne-bautenschutz.de

· Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi Irritant
- · Information concerning particular hazards for human and environment:

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

- · Hazard-determining components of labelling: Cement, portland, chemicals
- · Risk phrases:
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.

(Contd. on page 2)



Printing date 19.10.2012 Revision: 18.10.2012

Trade name: INTRASIT Poly-C1 54Z, powder

(Contd. of page 1)

10-20%

- · Safety phrases:
- 22 Do not breathe dust.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37/39 Wear suitable gloves and eye/face protection.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: cementitious reactive powder

· Dangerous o	components:
---------------	-------------

CAS: 65997-15-1 Cement, portland, chemicals

EINECS: 266-043-4 Xi R37/38-41

📀 Eye Dam. 1, H318; 🕦 Skin Irrit. 2, H315; STOT SE 3, H335

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Not applicable, product is not flammable.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Pick up mechanically.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Printing date 19.10.2012 Revision: 18.10.2012

Trade name: INTRASIT Poly-C1 54Z, powder

See Section 13 for disposal information.

(Contd. of page 2)

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling Avoid formation of dust.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Protected against ingress of moisture stored in closed rooms.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in dry conditions.
- $\cdot$  *Specific end use*(s) *No further relevant information available.*

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 65997-15-1 Cement, portland, chemicals (10-25%)

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

## 14808-60-7 Quartz (SiO2) (25-50%)

MAK 0.15 A mg/m<sup>3</sup> 24; Y; DFG

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: dust mask
- · Protection of hands: Protective gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Protective glasses.

GB



Printing date 19.10.2012 Revision: 18.10.2012

Trade name: INTRASIT Poly-C1 54Z, powder

(Contd. of page 3)

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Powder
Colour: Grey
Odourless

- pH-value at 20°C: 11.5
- · Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

- · Flash point: Not applicable.
- · Self-igniting: Product is not selfigniting.
- Danger of explosion: Product does not present an explosion hazard.
- · Density: Not determined.
- · Solubility in / Miscibility with

water at 20°C: dispersible

· Solvent content:

Organic solvents: 0.0 %

• Other information No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization:

As long as the expiration date of the product is not exceeded, a sensitizing effect is not expected.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

GB



Printing date 19.10.2012 Revision: 18.10.2012

Trade name: INTRASIT Poly-C1 54Z, powder

(Contd. of page 4)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	-
· UN proper shipping name	-
· Transport hazard class(es)	-
· Packing group	-
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex . MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	Not dangerous for transport.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 6)



Printing date 19.10.2012 Revision: 18.10.2012

Trade name: INTRASIT Poly-C1 54Z, powder

(Contd. of page 5)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GR