

Page 1/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.06.2020 Revision: 30.06.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN E-PU 12P, Komp. B
- · Article number: 40141B
- · UFI: SUE0-N0W6-J006-A613
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

2-component, permanently elastic joint sealing compound for horizontal expansion joints, Comp. B

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 30.06.2020 Revision: 30.06.2020

### Trade name: HADALAN E-PU 12P, Komp. B

· Hazard pictograms





GHS07

#### · Signal word Danger

#### · Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

diphenylmethane-4,4'-di-isocyanante

diphenylmethane-2,4'-diisocyanate

diphenylmethane-2,2'-diisocyanate

#### · Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection. P280 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P312 Call a POISON CENTER/doctor if you feel unwell.

#### Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Isocyanate component

CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	25-50%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 101-68-8	diphenylmethane-4,4'-di-isocyanante	2.5-10%
EINECS: 202-966-0	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	

(Contd. of page 1)

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

CAS: 5873-54-1	diphenylmethane-2,4'-diisocyanate	2.5-10%
EINECS: 227-534-9	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
EINECS: 219-799-4	diphenylmethane-2,2'-diisocyanate  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<2.5%

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Foam (alcohol-resistant), carbon dioxide, powder, spray mist (water)
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear protective clothing. Possibly. Respirator required
- · Additional information Do not allow fire-fighting water to enter the sewage system

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected people away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Keep container tightly closed at 5 ° C to 30 ° C.

(Contd. on page 4)

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

(Contd. of page 3)

- Information about storage in one common storage facility: Keep away from food, drink and animal feed.
- · Further information about storage conditions:
- Always keep in the original container. Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues (25-50%)

WEL 0.05 mg/m<sup>3</sup> 29; DFG

#### 101-68-8 diphenylmethane-4,4'-di-isocyanante (2.5-10%)

WEL Long-term value:  $0.05 \text{ U mg / m}^3$ 1; = 2 = (I); DFG, 11, 12, H, Sah, Y

#### 5873-54-1 diphenylmethane-2,4'-diisocyanate (2.5-10%)

WEL Long-term value:  $0.05 \text{ mg} / m^3$ 1; = 2 = (I); AGS, 11, 12

#### 2536-05-2 diphenylmethane-2,2'-diisocyanate (<2.5%)

WEL Long-term value:  $0.05 \text{ mg} / m^3$ 1; = 2 = (I); AGS, 11, 12

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Colour: brownish

(Contd. on page 5)

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

		(Contd. of page
Odour:	Characteristic	
Change in condition		
Melting point/freezing point:	<i>-30</i> ° <i>C</i>	
Initial boiling point and boiling range:	>300 °C	
Flash point:	229 °C	
Ignition temperature:	520 °C	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Vapour pressure at 20 °C:	11 hPa	
Density at 20 °C:	1.24 g/cm³	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Viscosity:		
Dynamic at 20 °C:	145 mPas	
Kinematic:	Not applicable.	
Solvent content:		
Solids content:	100.0 %	
9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 6)

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

(Contd. of page 5)

· Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Allow individual components that are no longer usable in the prescribed mixing and harden. Disposal according to official regulations.

· European waste catalogue

08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· 14.4 Packing group		
· ADR, IMDĞ, İATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	

GB ·

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

(Contd. of page 6)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 52a, 56a, 56b
- · National regulations:
- · Technical instructions (air):

Class	Share in %
I	100%

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

From the European Committee of Paint, Printing Inks and Artists 'Paint Manufacturers' Associations - CEPE

the following information is given for paints containing isocyanate: ready-to-use paints, containing isocyanates can cause irritation to the mucous membranes - especially the respiratory system - exercise and trigger hypersensitivity reactions. When inhaling vapors or spray mist Risk of sensitization. When handling isocyanate-containing paints, all measures are for Solvent-based paints must be carefully observed. In particular, spray mist and vapors must not be inhaled. Allergy sufferers, asthmatics and people who are prone to respiratory diseases must not be used for work with paints containing isocyanate.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

(Contd. on page 8)

Page 8/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.06.2020 Revision: 30.06.2020

Trade name: HADALAN E-PU 12P, Komp. B

(Contd. of page 7)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

CD