

Printing date 28.09.2020 Revision: 28.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN EPUni 12E, Komp. A
- · Article number: 40231A
- · UFI: 9P50-K0AG-F005-GRNY
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Low-viscosity, solvent-free epoxy resin, component A (resin).
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0

info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

(Contd. on page 2)

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 1)

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

Epoxy resin

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	50-100%
	Aquatic Chronic 2, H411; () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%
CAS: 68609-97-2 EINECS: 271-846-0	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: RE 1 (resin + hardener)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available. (Contd. on page 3)

__ Gl

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Use fire extinguishing methods suitable to surrounding.

Foam (alcohol resistent), carbon dioxide, dry powder, water spray

- · For safety reasons unsuitable extinguishing agents: Water jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

No special measures required.

In case of fire: breathing protection with independent air supply.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away non-protected persons. Ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

Only store in original containers

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Keep cool and dry.
- · Information about storage in one common storage facility: Store separate from eatables
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: VCI: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not required.

With good ventilation not necessary.

· Protection of hands:

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Use protective gloves. Wear Nitrile gloves with a thickness of min. 0.4 mm.

(Breakthrough ³ 480 min. - See also www gisbau.de.)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve protection: Tightly sealed goggles
- · Body protection: Use long-sleeved protective clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical a	nd chemical properties
· General Information · Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	n.a.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	inge: >200 °C
· Flash point:	120 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	450 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.

(Contd. on page 5)

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

		(Contd. of page
Upper:	Not determined.	
· Vapour pressure at 50 °C:	<5 hPa	
Density at 20 °C:	1.12 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	600 mPas	
Kinematic:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Exothermic reactions with amines. Work quickly after adding the hardener, since at high curing temperatures can be achieved.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Keep away from highly acidic and alkaline materials, oxidizing agents to avoid exothermic reactions.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

At higher temperatures may produce carbon dioxide, carbon monoxide and nitrogen oxides.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50) values r	elevant fo	or classij	fication:
-----------	------------	------------	------------	-----------

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Dermal | LD50 | >2,000 mg/kg (rab) | >2,000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 5)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE
	LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), phenol, polymer with formaldehyde glycidyl ether)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol), MARIN. POLLUTANT

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

	(Contd. of page
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Hazard identification number (Kemler code): Stowage Category	90 A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU, SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESI (NUMBER AVERAGE MOLECULAR WEIGHT = 700) PHENOL, POLYMER WITH FORMALDEHYDE GLYCIDYL ETHER), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 8)

Printing date 28.09.2020 Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 7)

Other regulations, limitations and prohibitive regulations

For activities involving exposure to uncured epoxy resins and contact through the skin or the respiratory regular occupational medical examinations are to be taken.

The product subject to the directive 2004/42/EG. The VOC limit value of this product in ready to use condition is max. 500 g/l. The product contains in ready to use condition max. 1 g/l VOC.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- GB