

Printing date 30.10.2020 Revision: 30.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN ESD-LS 12E, Komponente A
- · **UFI:** GHW1-X03D-G00F-7T1E
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture 2 comp. Epoxy resin as ESD conductive layer, comp. A
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs

(Contd. on page 2)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of the substances listed below with harmless additions

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	25-50%
	Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	10-25%
	Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-25%
EINECS: 271-846-8	Skin Irrit. 2, H315; Skin Sens. 1, H317	

Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: RE 1 (resin + hardener)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Foam (alcohol resistant); Carbon dioxide, powder, spray mist
- · For safety reasons unsuitable extinguishing agents: Full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- **Protective equipment:** In the event of fire: Use respiratory protection with an independent fresh air supply.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people away, ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Store in a cool, dry place in tightly closed containers.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store container in a cool, well-ventilated place.
- · Information about storage in one common storage facility: Store away from food, beverages and feed.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) (50-75%)

WEL see. Section IIb

(Contd. on page 4)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required with good ventilation.
- · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Wear gloves made of nitrile with a layer thickness of > 0.4 mm (penetration time > = 480 min. - see also www.gisbau.de)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles • Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on	basic physical and	l chemicai	l properties

· General Information

· Appearance:

Form: Fluid
Colour: White

• Odour: Weak, characteristic
• Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** Undetermined.

• Flash point: $>60 \, ^{\circ}C$

· Flammability (solid, gas): Not applicable.

• Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

(Contd. on page 5)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

		(Contd. of page 4
· Density:	Not determined.	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Exotherme Reaktionen mit Aminen. Nach Zugabe des Härters zügig verarbeiten, da bei der Aushärtung hohe Temperaturen erreicht werden können.

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:

Keep away from strongly acidic and alkaline materials as well as oxidizing agents in order to avoid exothermic reactions.

· 10.6 Hazardous decomposition products:

At high temperatures, carbon dioxide, carbon monoxide, smoke and nitrogen oxides can be produced.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	LD/LC50 values relevant for classification:		
25068-3		action product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular ight = 700)	
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	mg/kg (rab)	
		>1,200 mg/kg (rat)	
9003-36	-5 forn	naldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
Oral	LD50	mg/kg (rab)	
		>1,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
68609-9	7-2 ox	irane, mono[(C12-14-alkyloxy)methyl] derivs	
Oral	LD50	mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rat)	
Primary	irritan	nt effect:	

- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 6)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 5)

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

The product must be regarded as dangerous for the environment and is toxic to the living things in the water. To cause negative effects in the aquatic environment in the long run.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

LC50 - fish 2.54 mg/l/96h (leuciscus idus)

EC50 - algae / aquatic plants 1.8 mg / l / 72h (algae)

EC10 crustaceans 2.55 mg/l/48h (daphnia)

Oxirane, mono [(C12-14-alkyloxy) methyl] derivatives

LC50 - fish> 10 mg/l/96h (leuciscus idus)

EC50 - crustaceans> 10 mg/l/48h (Dap)

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability

REACTION PRODUCT: BISPHENOL-A-EPICHLORHYDRINE RESINS

Not rapidly degradable

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Not rapidly degradable

Oxirane, mono [(C12-14-alkyloxy) methyl] derivatives

Quickly degradable

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 6)

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE
	LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl
	propane, formaldehyde, oligomeric reaction products wit
	1-chloro-2,3-epoxypropane and phenol)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE
	LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)pheny
	propane, formaldehyde, oligomeric reaction products with
	1-chloro-2,3-epoxypropane and phenol), MARIN POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE
IAIA	LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl
	propane, formaldehyde, oligomeric reaction products with
	1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
1	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
	articles.
Hazard identification number (Kemler code):	90 E 4 S E
EMS Number: Stowage Category	F-A,S-F A
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	- -
IMDG	
Limited quantities (LQ)	5L
	(Contd. on page

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

	(Contd. of page 7)
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients are included.
- · Seveso category E2 Hazardous to the aquatic environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Other regulations, limitations and prohibitive regulations

Regular preventive examinations must be arranged for activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract.

The product is subject to RL 2004/42 / EG. EU limit value for this product is in the ready-to-use condition: Cat A/j max. 500 g/l (2010). When used, the product contains: max. 1 g/l VOC.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

Printing date 30.10.2020 Revision: 30.10.2020

Trade name: HADALAN ESD-LS 12E, Komponente A

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - dermal - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2: Skin sensitisation - Category 2
Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB