Printing date 12.10.2020 Revision: 01.07.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: HADALAN GVS 12E, Komp. B

· Article number: 40637B

· UFI: WD40-Y0YH-U00R-JMX0

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Primer, gradient and protective coating colored, 2-component. Epoxy resin.

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück

Tel.: +49 2363 5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS05

GHS07

GHS09

· Signal word Danger

(Contd. on page 2)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

(Contd. of page 1)

· Hazard-determining components of labelling:

Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated

3-aminopropyldiethylamine

formaldehyde, oligomeric reaction products with phenol

1,3-benzenedimethanamine, N-(2-phenylethyl) derivs.

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone		
CAS: 1173092-74-4	Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	50-75%
	Skin Corr. 1C, H314; 🔖 Aquatic Acute 1, H400; Aquatic Chronic 2, H411; 🐧 Acute Tox. 4, H302; Skin Sens. 1, H317	
CAS: 9003-35-4	formaldehyde, oligomeric reaction products with phenol	10-25%
	t Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 104-78-9	3-aminopropyldiethylamine	2.5-10%
EINECS: 203-236-4	♠ Flam. Liq. 3, H226; ♠ Skin Corr. 1B, H314; ♠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
CAS: 404362-22-7	1,3-benzenedimethanamine, N-(2-phenylethyl) derivs.	2.5-10%
	♦ STOT RE 2, H373; ♦ Skin Corr. 1B, H314; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ↑ Acute Tox. 4, H302; Skin Sens. 1, H317	

Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: RE 1 (resin + hardener)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

(Contd. of page 2)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

not applicable, product is not flammable

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Ingredients with biological limit values:

100-51-6 Benzyl alcohol (2.5-10%)

WEL | Long-term value: 22 mg/m³, 5 ml/m³ 2 (I); DFG, H, Y, 11

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Appearance:

Form: Fluid

Colour: According to product specification

• Odour: Characteristic
• Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

		(Contd. of page
Change in condition Melting point/freezing point: Initial boiling point and boiling range.	Undetermined. : 201°C	
Flash point:	101 °C	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure at 21 °C:	>0 hPa	
Density at 20 °C:	1.01 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Solids content:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed.

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

(Contd. of page 5)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: T	ransport in	iformation
---------------	-------------	------------

. 11	1 IIN.	-Number	,

· ADR, IMDG, IATA UN2735

· 14.2 UN proper shipping name

ADD

ADR 2735 AMINES, LIQUID, CORROSIVE, N.O.S., ENVIRONMENTALLY HAZARDOUS

· IMDG, IATA AMINES, LIQUID, CORROSIVE, N.O.S.

· 14.3 Transport hazard class(es)

· ADR



Class 8 *Corrosive substances.*

(Contd. on page 7)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

	(Contd. of page
Label	8
· IMDG, IATA	
Class Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80 E 4 C B
· EMS Number: · Stowage Category	F-A,S-B A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex II o	nf .
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S., 8, II ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

For activities involving exposure to uncured epoxy resins and contact with the skin or the Respiratory tract are to be arranged for regular preventive examinations. The product is subject to the RL 2004/42 / EG.EU limit value of this product is ready to use: Cat A/j max. 500 g/l (2010). When ready for use, the product contains: max. l g/l VOC.

(Contd. on page 8)

Printing date 12.10.2020 Revision: 01.07.2020

Trade name: HADALAN GVS 12E, Komp. B

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3