Page 1/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2021 Revision: 13.07.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN LF41 12E, Komp. A
- · Article number: 40378A
- · UFI: 7Y30-F0HJ-A008-8X0P
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Solvent-free, 2-component epoxy resin coating for floors and wall surfaces, outside and inside, component A.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS05



· Signal word Danger

(Contd. on page 2)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Epoxidharz-Aminaddukt

Fettsäuren, Tallöl-, Reaktionsprodukte mit Tetraethylenpentamin

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

#### · Additional information:

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of the substances listed below with harmless additions

· Dangerous compone	ents:	
CAS: 260549-92-6	Epoxidharz-Aminaddukt	10-25%
	♦ Eye Dam. 1, H318	
	titanium dioxide	2.5-10%
EINECS: 236-675-5	<b>♦</b> Carc. 2, H351	
	Fettsäuren, Tallöl-, Reaktionsprodukte mit Tetraethylenpentamin	<2.5%
	Skin Corr. 1C, H314; Eye Dam. 1, H318; 🚱 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🐧 Skin Sens. 1, H317	

#### · Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE:  $RE\ 1$  (Komp. A+B)

### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

ivo juriner retevant injormation avaitable.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Extinguishing measures are to be coordinated with the surrounding fire.

- · 5.2 Special hazards arising from the substance or mixture Nitrogen oxides (NOx)
- · 5.3 Advice for firefighters
- · Protective equipment: Wear full protective suit.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Remove people. Provide adequate ventilation.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use and open container with care
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the unopened original container.
- · Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

### 13463-67-7 titanium dioxide (2.5-10%)

WEL Long-term value: 10\* 4\*\* mg/m³ \*total inhalable \*\*respirable

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

· Density at 20 °C:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Wear nitrile gloves with a layer thickness of > 0.4 mm (penetration time <sup>3</sup> 480 min. - see also www.gisbau.de)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles • Body protection: Protective work clothing.

SECTION 9: PI	ysical and	chemical	properties
---------------	------------	----------	------------

SECTION 7. I hysical and th	ienteut properties	
· 9.1 Information on basic physical a	and chemical properties	
· General Information		
· Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	9.5	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling re	ange: 100 °C	
· Flash point:	Not applicable.	
· Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	

 $1.65 \, g/cm^3$ 

(Contd. on page 5)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	30.0 %	
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Irritant

Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 5)

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	-
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	-
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	-
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	-
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)

Printing date 15.07.2021 Revision: 13.07.2020

Trade name: HADALAN LF41 12E, Komp. A

(Contd. of page 6)

#### · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

Regular occupational medical examinations must be arranged for activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract.

The product is subject to RL 2004/42 / EG.

EU limit value for the VOC content of this product in ready-to-use state: Cat. A/j 140 g/l (2010).

*The ready-to-use product contains: max. 1 g / l VOC.* 

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

 ${\it Skin \ Corr. \ 1C: Skin \ corrosion/irritation-Category \ 1C}$ 

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB