

Revision: 29.09.2020

Page 1/8

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.09.2020 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: HADALAN MBH 12E, Komp. A · Article number: 40377 · UFI: 2H30-X02J-S00T-X73C · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Solvent-free, 2-component epoxy resin, resin component. • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Sievert Baustoffe GmbH & Co. KG Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0 • Further information obtainable from: Abteilung: Produktsicherheit

Tel.. +49 2363 5663-0 info-hahne@sievert.de · 1.4 Emergency telephone number: Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen, Tel.: 0551-19240

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

# GHS07

Skin Irrit. 2	H315 Causes skin irritation.	
Eye Irrit. 2	H319 Causes serious eye irritation.	
Skin Sens. 1	H317 May cause an allergic skin reaction	n.

· 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

(Contd. on page 2)

GB

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

#### Trade name: HADALAN MBH 12E, Komp. A

	(Contd. of page 1)
formaldehyde, oligomeric reaction products with 1-chlo	pro-2,3-epoxypropane and phenol
oxirane, mono[(C12-14-alkyloxy)methyl] derivs Hazard statements	
H315 Causes skin irritation.	
H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.	
H411 Toxic to aquatic life with long lasting effects.	
Precautionary statements	
<i>P262</i> Do not get in eyes, on skin, or on clothing.	
<i>P273 Avoid release to the environment.</i>	
P280 Wear protective gloves/protective clothing	/eve protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POI	
P333+P313 If skin irritation or rash occurs: Get medic	
P360 Rinse immediately contaminated clothing of	and skin with plenty of water before removing clothes.
Additional information:	
Contains epoxy constituents. May produce an allergic n	reaction.
2.3 Other hazards	
Results of PBT and vPvB assessment	
<b>PBT:</b> Not applicable.	
vPvB: Not applicable.	

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions

· Dangerous components:			
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	50-100%	
	Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 9003-36-5	CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3 epoxypropane and phenol		
	Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317		
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-25%	
EINECS: 271-846-8	🚯 Skin Irrit. 2, H315; Skin Sens. 1, H317		
Additional information:			

Additional information:

For the wording of the listed hazard phrases refer to section 16. GISCODE: RE 1 (resin + hardener)

#### **SECTION 4:** First aid measures

• 4.1 Description of first aid measures

· General information: Remove contaminated clothing immediately.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.* • *After swallowing:* Drink plenty of water and provide fresh air. Call for a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

GB

Page 3/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

#### Trade name: HADALAN MBH 12E, Komp. A

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Foam (alcohol resistant), carbon dioxide, powder, spray

- For safety reasons unsuitable extinguishing agents: 'Water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: In case of fire: Use breathing apparatus with independent air supply.

#### **SECTION 6:** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Keep people away, provide adequate ventilation.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Store in tightly closed containers in a cool, dry place.

- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Keep container in a cool, well-ventilated place.
- Information about storage in one common storage facility: Store away from foodstuffs, beverages and feed.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: VCI: 10
- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection: If good ventilation is not required.

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

(Contd. of page 3)

#### Trade name: HADALAN MBH 12E, Komp. A

#### · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Nitrile gloves with a thickness of > 0,4 mm wear (breakthrough time 480 min <sup>3</sup>-see also www.gisbau.de) · *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed goggles

· Body protection: Protective clothing

SECTION 9: Physical and chem	nical properties
9.1 Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	colorless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	<i>n.a.</i>
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	<i>e</i> : ≥200 °C
Flash point:	120 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	450 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.12 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 5)

GB

Page 5/8

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

(Contd. of page 4)

#### Trade name: HADALAN MBH 12E, Komp. A

• 9.2 Other information

No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- *Thermal decomposition / conditions to be avoided:* No decomposition if used according to specifications. • 10.3 Possibility of hazardous reactions
- Exothermic reactions with amines. Processed quickly after adding the hardener, since in the high curing temperatures can be achieved.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:

From highly acidic or alkaline materials as well as oxidizers away to avoid exothermic reactions.

• 10.6 Hazardous decomposition products:

At high temperatures, carbon monoxide and dioxide, smoke and oxides of nitrogen.

#### SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation. • **Respiratory or skin sensitisation**
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot$  **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-repeated exposure} \textit{ Based on available data, the classification criteria are not met.}$
- · Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

Page 6/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

Trade name: HADALAN MBH 12E, Komp. A

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 5)

GB

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.* 

14.1 UN-Number ADR, IMDG, IATA	UN3082
	0110002
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE
ADA	LIQUID, N.O.S. (reaction product: bisphenol-A
	(epichlorhydrin) epoxy resin (number average molecula
	weight = $700$ ), phenol, polymer with formaldehydd
	glycidyl ether)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A
	(epichlorhydrin) epoxy resin (number average molecula
	weight = 700), formaldehyde, oligomeric reaction produc
	with 1-chloro-2,3-epoxypropane and phenol), MARIN
	POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE
	LIQUID, N.O.S. (reaction product: bisphenol-A
	(epichlorhydrin) epoxy resin (number average molecula weight = 700), formaldehyde, oligomeric reaction produc
	with 1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR	111
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
	articles. 90
Hazard identification number (Kemler code):	

Page 7/8

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

#### Trade name: HADALAN MBH 12E, Komp. A

	(Contd. of page
Stowage Category	A
· 14.7 Transport in bulk according to Anna	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
U U	SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT
	BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESI
	(NUMBER AVERAGE MOLECULAR WEIGHT = 700)
	PHENOL, POLYMER WITH FORMALDEHYDE
	GLYCIDYL ETHER), 9, III

### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• Other regulations, limitations and prohibitive regulations

For activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract regular checkups are causing.

The product is subject RL 2004/42/EG.EU-Grenzwert this product is used in the manufacture condition: Cat A / j max. 500 g / l (2010). The product contains used in the finished state: max. 1 g / l VOC.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 8)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2020

Revision: 29.09.2020

# Trade name: HADALAN MBH 12E, Komp. A

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	(Contd. of page 7)
Aquatic Chronic 2: Hazaraous to the aquatic environment - long-term aquatic hazara – Category 2	GB