

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2021 Revision: 28.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN VS 12E, Komp. A
- · Article number: 40239A
- · UFI: 0470-6027-N00K-RJK2
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Solvent-free, 2-component epoxy resin floor coating for areas with high mechanical and chemical stress.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS09

· Signal word Warning

(Contd. on page 2)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

(Contd. of page 1)

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P360 Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of the substances listed below with harmless additions

· Dangerous components:			
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	25-50%	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.5-10%	
	🕸 Aquatic Chronic 2, H411; 🕦 Skin Irrit. 2, H315; Skin Sens. 1, H317		
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	2.5-10%	
EINECS: 271-846-8	♦ Skin Irrit. 2, H315; Skin Sens. 1, H317		
CAS: 13463-67-7	titanium dioxide	2.5-10%	
EINECS: 236-675-5	♦ Carc. 2, H351		

Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: $RE\ 1$ (Komp. A+B)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Remove contaminated clothing immediately.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

(Contd. of page 2)

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Foam (alcohol resistant); Carbon dioxide, powder, spray mist

- · For safety reasons unsuitable extinguishing agents: Full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: In the event of fire: Use breathing protection with an independent fresh air supply.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people away, ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Store in a cool, dry place in tightly closed containers.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store container in a cool, well-ventilated place.
- · Information about storage in one common storage facility: Store away from food, drink and animal feed.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: VCI: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

13463-67-7 titanium dioxide (2.5-10%)

WEL Long-term value: 10* 4** mg/m³ *total inhalable **respirable

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required with good ventilation.
- · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Wear nitrile gloves with a layer thickness of > 0.4 mm (penetration time > = 480 minutes - see also www.gisbau.de)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eve protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical are General Information	w chemica properties	
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	n.a.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	nge: >200 °C	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	450 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	$1.6 \mathrm{g/cm^3}$	

(Contd. on page 5)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	9,500 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Exothermic reactions with amines. Process quickly after adding the hardener, as high temperatures can be reached during the hardening process.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Keep away from strongly acidic and alkaline materials as well as oxidizing agents in order to avoid exothermic reactions.

· 10.6 Hazardous decomposition products:

At high temperatures, carbon dioxide, carbon monoxide, smoke and nitrogen oxides can be produced.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:			
25068-3	25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecula weight = 700)			
Oral	LD50	>2,000 mg/kg (rat)		
Dermal	LD50	mg/kg (rab)		
		>2.00 mg/kg (rat)		

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

(Contd. of page 5)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
·ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCL LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), formaldehyde, oligomeric reaction produc with 1-chloro-2,3-epoxypropane and phenol), MARIN POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average moleculo weight = 700), formaldehyde, oligomeric reaction product

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

	(Contd. of page
	with 1-chloro-2,3-epoxypropane and phenol)
· 14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Hazard identification number (Kemler code):	articles. 90
Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	p f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU, SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESID (NUMBER AVERAGE MOLECULAR WEIGHT = 700) FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPAND AND PHENOL), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 8)

Printing date 15.07.2021 Revision: 28.09.2020

Trade name: HADALAN VS 12E, Komp. A

(Contd. of page 7)

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Other regulations, limitations and prohibitive regulations

Regular occupational medical examinations must be arranged for activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract.

Substances of very high concern (SVHC) according to REACH, Article 57

Das Produkt unterliegt der RL 2004/42/EG.EU-Grenzwert dieses Produktes ist im gebrauchtfertigen Zustand: Kat A/j max. 500 g/l (2010). Das Produkt enthält im gebrauchtfertigen Zustand: max. 1 g/l VOC.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB