

Printing date 24.11.2020 Revision: 24.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HADALAN WHG-G 12E, Komponente B
- · **UFI:** HVU0-K0TJ-300E-V2KW
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture 2 comp. Epoxy resin as WHG primer, Comp. B
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05

GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 1)

· Hazard-determining components of labelling:

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane

Benzyl alcohol

m-phenylenebis(*methylamine*)

2-piperazin-1-ylethylamine

· Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage. H314

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P273 Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- · 2.3 Other hazards EUH071 Wirkt ätzend auf die Atemwege.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Amine-containing hardener for epoxy resins.

Dangerous compone	ents:	
CAS: 38294-64-3	Phenol, 4,4'-(I-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane	25-50%
	Skin Corr. 1B, H314; Eye Dam. 1, H318; 🕩 Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 100-51-6	Benzyl alcohol	10-25%
EINECS: 202-859-9	(1) Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 1477-55-0	m-phenylenebis(methylamine)	10-25%
EINECS: 216-032-5	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 122-99-6	2-Phenoxyethanol	2.5-10%
EINECS: 204-589-7	(1) Acute Tox. 4, H302; Eye Irrit. 2, H319	
CAS: 140-31-8	2-piperazin-1-ylethylamine	2.5-10%
EINECS: 205-411-0	Skin Corr. 1B, H314;	
CAS: 69-72-7	salicylic acid	<2.5%
EINECS: 200-712-3	♦ Repr. 2, H361d; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	<2.5%
EINECS: 202-013-9	♦ Skin Corr. 1B, H314;	
CAS: 104-68-7	2-(2-phenoxyethoxy)ethanol	<2.5%
	♦ Eye Dam. 1, H318	

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 2)

GISCODE: RE 1 (Harz + Härter)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Foam (alcohol-resistant), carbon dioxide, powder, spray mist.
- · For safety reasons unsuitable extinguishing agents: Full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Store in a cool and dry place.

• Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Store away from food, beverages and feed.
- · Further information about storage conditions:

Keep container tightly sealed.

Store frost-free.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

	o.i control parameters				
	· Ingredients with limit values that require monitoring at the workplace:				
	100-51-6 Benzyl alcohol (10-25%)				
	WEL Long-term value: 22 mg / m³, 5 ml / m³ 2 (I); DFG, H, Y, 11				
Г	1477-55-0 m-phenylenebis(methylamine) (10-25%)				
	WEL as vapor and aerosol; see Section IV				
	122-99-6 2-Phenoxyethanol (2.5-10%)				
	WEL Long-term value: 5.7 mg / m³, 1 ml / m³ 1 (1): DFG, Y, 11				

· PNECs

BENZYL ALCOHOL

Reference value in fresh water 1 mg/l

Reference value in sea water 0.1 mg/l

Reference value for deposits in fresh water 5.27 mg / kg

Reference value for deposits in sea water 0.527 mg / l

Water reference value, intermittent release 2.3 mg / l

Reference value for microorganisms STP 39 mg / l

Reference value for earthly creatures $0.456 \ mg \ / \ kg$

M-PHENYLENBIS (METHYLAMINE)

Reference value in fresh water 0.094 mg / l

Reference value in sea water 0.0094 mg/l

Reference value for deposits in fresh water 0.043 mg/kg/d

Reference value for deposits in sea water 0.0043 mg / kg / d $\,$

Water reference value, intermittent release 0.152 mg/l

Reference value for microorganisms STP 10 mg / l

Reference value for earthly creatures 0.0278 mg/kg/d

Reference value in fresh water 0.2 mg / l

Reference value in sea water 0.02 mg / l

Reference value for deposits in fresh water 1.42 mg/kg

Reference value for deposits in sea water 0.142 mg/kg

Water reference value, intermittent release 1 mg/l

Reference value for microorganisms STP 162 mg/l

Reference value for earthly creatures 0.166 mg / kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

(Contd. on page 5)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 4)

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not required with good ventilation. Wear respiratory protection at workplaces that are not adequately ventilated and when spraying. Filter A/P2.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Reagent protective nitrile gloves with a layer thickness of at least 0.4 mm (penetration shows> 480 min. See also www.gisbau.de).

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Tightly sealed goggles
- · Body protection: Wear long-sleeved protective clothing.

SECTION 9: Physical and chemical properties		
· 9.1 Information on basic physical and co · General Information · Appearance:	hemical properties	
Form:	liquid	
Colour:	yellowish	
· Odour:	after Amin.	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/freezing point: Initial boiling point and boiling range.	Undetermined. : 205.4 °C	
· Flash point:	>60 °C	
· Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	1.3 Vol %	
Upper:	13 Vol %	
· Vapour pressure at 20 °C:	0.1 hPa	
· Density:	Not determined.	
· Relative density	Not determined.	
· Vapour density	Not determined.	

(Contd. on page 6)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

		(Contd. of page .
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Keep away from strongly acidic and alkaline materials as well as oxidizing agents in order to avoid exothermic reactions.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

LC50 (inhalation) of the mixture: > 20 mg/lLD50 (oral) of the mixture: 1310.56 mg/kg LD50 (dermal) of the mixture: > 2000 mg / kg

· Acute toxicity

Harmful if swallowed or if inhaled.

LD/LC50	values rele	vant for classification:
1477-55-0	m-phenyle	enebis(methylamine)
Oral	LD50	1,040 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rab)
Inhalative	LC50/4 h	2.4 mg/l (rat)
100-51-6 Benzyl alcohol		
Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	4,178 mg/l (rat)
38294-64-		1, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3
	trimethy	lcyclohexanemethanamine and (chloromethyl)oxirane
Oral	LD50	2169 mg/kg (rat)
69-72-7 salicylic acid		
Oral	LD50	891 mg/kg (rat)
Inhalative	LC50	>0.9 mg/l (rat)
140-31-8 2-piperazin-1-ylethylamine		
Oral	LD50	1,470 mg/kg (Rat)
Dermal	LD50	866 mg/kg (rbt)
Primary ir	ritant effe	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 7)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 6)

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

M-PHENYLENBIS(METHYLAMIN)

LC50 - Fische 87,6 mg/l/96h Oryzias latipes

EC50 - Krustentiere 15,2 mg/l/48h Daphnia magna

EC50 - Algen / Wasserpflanzen 20,3 mg/l/72h Pseudokirchnerella subcapitata

BENZYLALKOHOL

LC50 - Fische 460 mg/l/96h Pimephales promelas

EC50 - Krustentiere 230 mg/l/48h Daphnia magna

EC10 Algen / Wasserpflanzen 700 mg/l/72h Pseudokirchneriella subcapitata

NOEC chronisch Krustentiere 51 mg/l Daphnia magna

Salicylsäure

LC50 - Fische 90 mg/l/96h Leuciscus idus melanotus

EC50 - Krustentiere 870 mg/l/48h Daphnia magna

EC50 - Algen / Wasserpflanzen > 100 mg/l/72h Scenedesmus subspicatus

2,4,6-TRI-(DIMETHYLAMINOMETHYL) PHENOL

LC50 - Fische 175 mg/l/96h (Cyprinus carpio

EC50 - Algen / Wasserpflanzen 84 mg/l/72h (Scenedesmus subspicatus)

2-Piperazin-1-ylethylamin

LC50 - Fische 368 mg/l/96h Poecilia reticulata

EC50 - Krustentiere > 32 mg/l/48h Daphnia magna

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability

M-PHENYLENBIS (METHYLAMINE) Solubility in water 1000 - 10000 mg / l Rapidly degradable

2-PHENOXYETHANOL Solubility in water 28600 mg / l Rapidly degradable

BENZYL ALCOHOL Rapidly degradable

Salicylic Acid Inherently degradable

2-piperazin-1-ylethylamine is NOT rapidly degradable

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

 ${\it Must not reach sewage water or drainage ditch undiluted or unneutralised}.$

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 8)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 7)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number	
ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name	
ADR	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (n
	phenylenebis (methylamine), N
NO CALE	AMINOETHYLPIPERAZINE)
IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (nphenylenebis (methylamine). N
	phenylenebis (methylamine), N AMINOETHYLPIPERAZINE)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group	
ADR, IMDG, IATA	I
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	88
EMS Number:	F-A,S-B
Segregation groups Stowage Category	Alkalis A
Significant Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex II o	of .
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0
Tugues out estacom	Not permitted as Excepted Quantity
Transport category Tunnel restriction code	I E

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 8) · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE), N-AMINOETHYLPIPERAZINE), 8, I

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients are included.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	4,0

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Other regulations, limitations and prohibitive regulations

Regular preventive examinations must be arranged for activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eve damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 10)

Printing date 24.11.2020 Revision: 24.11.2020

Trade name: HADALAN WHG-G 12E, Komponente B

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4
Skin Corr. 1B: Skin corrosion/irritation - Category 1B
Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3