

Printing date 10.09.2020 Revision: 10.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: IMBERAL DAB 30P
- · Article number: 40567
- · UFI: REE0-40F7-000Q-1G3S
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture 1-comp. Liquid plastic for seamless, elastic sealing of details.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sievert Baustoffe GmbH & Co. KG

Mühleneschweg 6 D-49090 Osnabrück Tel.: +49 2363 5663-0

· Further information obtainable from:

Abteilung: Produktsicherheit Tel.. +49 2363 5663-0 info-hahne@sievert.de

· 1.4 Emergency telephone number:

Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,

Tel.: 0551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

(Contd. of page 1)

· Hazard pictograms







GHS02

GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Aromatisches Polyisocyanat-Prepolymer

xylene, mixed isomers, pure

4-methyl-m-phenylene diisocyanate

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions:

· Dangerous components:		
CAS: 37273-56-6	Aromatisches Polyisocyanat-Prepolymer	25-50%
	♦ Resp. Sens. 1, H334; ♦ Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 1330-20-7	xylene, mixed isomers, pure	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	<2.5%
EINECS: 203-603-9	♠ Flam. Liq. 3, H226	
CAS: 53880-05-0	Isophorondiisocyanat Homopolymer	<2.5%
	♦ Skin Sens. 1, H317; STOT SE 3, H335	

(Contd. on page 3)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

CAS: 77-58-7	dibutyltin dilaurate	< 0.25
EINECS: 201-039-8	Acute Tox. 3, H301; & Muta. 2, H341; Repr. 1B, H360FD; STOT RE 1, H372	
	4-methyl-m-phenylene diisocyanate	< 0.25
	Acute Tox. 2, H330; & Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	

For the wording of the listed hazard phrases refer to section 16.

GISCODE: PU50

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Foam, carbon dioxide, dry chemical, water fog, spray

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters

Do not breathe explosion and fire fumes.

Wear self-contained breathing apparatus.

· Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective equipment. Keep spectators away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Open and handle receptacle with care.

Ensure adequate ventilation in the workplace

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat and direct sunlight

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store on cool and dry place.
- · Information about storage in one common storage facility: Store away from foodstuffs
- · Further information about storage conditions:

Keep containers dry and prevent reaction with atmospheric moisture.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with l	imit values that re	quire monitoring a	t the workplace:
----------------------	---------------------	--------------------	------------------

108-65-6 2-methoxy-1-methylethyl acetate (<1.0%)

WEL Long-term value: $270 \text{ mg} / \text{m}^3$, $50 \text{ ml} / \text{m}^3$

1 (I); DFG, EU, Y

1330-20-7 xylene, mixed isomers, pure (2.5-10%)

WEL Long-term value: 440 mg/m³, 100 ml/m³

2 (II); DFG, EU, H

77-58-7 dibutyltin dilaurate (<0.25%)

WEL Long-term value: 0.009 mg/m^3 , 0.0018 ml/m^3

1 (I); H, Z, 10, 11, AGS

584-84-9 4-methyl-m-phenylene diisocyanate (<0.25%)

WEL Long-term value: 0.035 mg/m^3 , 0.005 ml/m^3

1; = 4 = (I); AGS, 11, 12, Sa

· Ingredients with biological limit values:

1330-20-7 xylene, mixed isomers, pure (2.5-10%)

 $BMGV \mid 1.5 \text{ mg} / l$

Test material: whole blood

Sampling time: end of exposure or end of shift

Parameter: xylene 2000 mg/L

Test material: urine

Sampling time: end of exposure or end of shift Parameter: methylhippur (toluric) acid (all isomers)

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

(Contd. of page 4)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

With good ventilation is not required

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves material: PVC, nitrile rubber.

· Material of gloves

· Explosion limits:

Lower:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical ar General Information 	nd chemical properties
Appearance:	
Form:	Fluid
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	nge: 146 °C
Flash point:	44 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	500 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive as vapour mixtures are possible. The product is not explosive, but the formation of explosive vapour.

1.5 Vol %

(Contd. on page 6)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

		(Contd. of page
Upper:	10 Vol %	
· Vapour pressure at 25 °C:	3.8 hPa	
· Density at 20 °C:	1.6 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	5,000 mPas	
Xinematic:	Not determined.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eve irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

(Contd. of page 6)

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

	tion	
14.1 UN-Number		
ADR, IMDG	Void	
IATA	UN1139	
14.2 UN proper shipping name		
ADR, IMDG	Void	
IATA	COATING SOLUTION	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG		
Class	Void	
IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG	Void	
IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

(Contd. of page 7)

• UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20, 52a
- · Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

- · National regulations:
- · Technical instructions (air):

Class	Share in %
I	0.2
NK	9.0

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Other regulations, limitations and prohibitive regulations

no flammable liquid in terms of the ordinance on flammable liquids (VbF)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H351 Suspected of causing cancer.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Printing date 10.09.2020 Revision: 10.09.2020

Trade name: IMBERAL DAB 30P

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 4: Acute toxicity - dermal - Category 4 Acute Tox. 2: Acute toxicity - inhalation - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

(Contd. of page 8)